

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - L.L. Williams and A.R. Flint under Contract #151 dated May 23, 1871 (DCSO records, Volume 10 Page 4377)

-----  
Set post to ¼ sec. cor., from which  
A Cedar 18" dia., bears S.45°W., 60 lks. dist.  
A Cedar 10" dia., bears N.10°W., 34 lks dist.

Doug. County Surveyors Office - James W. Byron, Deputy Milo Godfrey; Clete Putnam - Sept. 15, 1959, C.S. 49/48-5

-----  
Found - Orig. 10" now 22" Cedar N.10°W., 22.4 ft. I open and find good scribing "S".

No trace of original SW BT found.

Set brass cap at cor. mkd. County Surveyors Office, 1959

¼  $\frac{S\ 22}{S\ 27}$  T26S R3W

New BTs - 12" R.Fir bears N.30°W., 28.0 ft. scribed ¼ S22 CSBT

14" R.Fir bears S.65°E., 61.0 ft. scribed ¼ S27 CSBT

Found BC and 3 BT's - Bureau of Land Management dependent Resurvey by Berry; Popken and Carlson - Group #768 - Survey June 1972-April 1975 (DCSO records, Volume 37 pages 15404-05)

Cor. Fd & used in BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, under Group #1608, surveyed July 1991/April 1995 (DCSO records Vol. 51 page 19299)

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2268, Surveyed July/Nov. 2009 - DCSO records Vol. 57 Page(s) 22708

-----  
The ¼ sec. cor. of secs. 22 and 27, monumented with an iron post, 1¼" dia., firmly set, projecting 17" above the ground, in a collar of stone, with brass cap (properly) mkd.

from which the remains of an original bearing tree

A sawed cedar stump, 25" dia., bears N.10°W., 22.4 ft., with fragmentary scribe marks visible on an opened blaze.

and BTs mkd. by James W. Byron, in 1959

A fir, 21" dia., bears S.64½°E., 60.7 ft., with a healed double blaze. (Record, S.63°E.)

A fir, 26" dia., bears N.30°W., 26.4 ft., with a healed double blaze.