

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W. H. Byars, Under Contract #269 dated July 24, 1877 (DCSO records, Vol. 10 Pages 4378-79)

Set a Fir post, 4" dia., 4 ft. long, 2" in the ground, from which

A Cedar 8" dia., bears N.24°E., 18 lks. dist.

A Cedar 8" dia., bears S.64°E., 30 lks. dist.

G.G. Stewart, For: C.J. Green - Wit: Max Shellabarger; M.L. Kimmel - March 18, 1922 - Vol. 3 Page 114

Set Corner half-way between section corners. All signs of BTs gone.

Set 2" Pipe, from which

Cedar 12" S.15°E., 65 ft.

Maple 18" N.31°E., 22 ft.

A.R.Evans - Dec. 1951 - C.S. File 41/26, M 13-31

Set ½" Pipe for corner by proper measurement.

Blaze and scribe two BTs:

8" Fir S.1°38'W., 17.4 ft. mkd. ¼ S Sec. 15 BT.

12" Fir N.67°33'W., 15.6 ft. mkd. ¼S Sec. 10 BT.

Copper tags and tacks in roots marked RE 2741.

Bureau of Land Management resurvey by White; Beck & Reynolds Group #'s 242, 491, 527. Survey June 1962-Aug. 1963 (DCSO records, Vol. 32 Pages 13387-88)

The ¼ sec. cor. of secs. 10 and 15, reestablished by proportionate measurement, by A.R. Evans in 1951, monumented with an iron pipe ½" dia., firmly set, protruding 4" above the ground, from which the bearing trees marked by Evans:

A Fir 17" dia., bears N.67°W., 24 lks. dist., with a healed blaze.

A Fir 12" dia., bears S.1°W., 26 lks. dist., with a healed blaze.

At the corner point, Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.

(Cont. Next Page)

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sections 10 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

<p>T 26 S R 3 W <u>S 10</u> ¼ <u>S 15</u> 1962</p> <p>Reset the local Iron pipe inside the iron post.</p>
<p>Found and Used, BLM Subdivision Section 15, by Bishop and Rogers, July-Sept. 1984 (DCSO Records, Vol. 47 Pgs. 17897-17898)</p>
<p>Bruce Shaner - for Johann Spross - Feb. 1993 - M 116 - 51; C.S. File 63/149-4A</p> <p>-----</p> <p>Found - 3¼" Brass Cap on a 2½" iron pipe, U.S. B.L.M. 28" D.Fir BT, face overgrown, bears N.64°W., (rec. N.67°W), 15.8'. 16" D.Fir BT, face overgrown, bears S.5°W., (rec. S.1°W.) 17.2'. New - 8" D.Fir, bears N.22°E., 6.8'. Scribed "¼ S10 BT". 10" D.Fir, bears S.56°E., 22.6'. Scribed "¼ S15 BT". Note - Located approx. 300' west and 50' north of gate on U.S.B.L.M. road.</p>
<p>Found OK Dec.1993 by M.Heimbürger - M119-13 FD. BC & 4 BTs by Carl Sweeden, 2/2006 - M149-57</p>