TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, Under Contract #269 dated July 24, 1877 (DCSO records, Vol. 10 Pages 4380-81)

Set an Oak post, 36" long, 5" dia., 18" in the ground, for the ¼ sec. cor., from which
A Laurel 36" dia., bears North, 26 lks. dist.
A Laurel 8" dia., bears S.65°W., 60 lks. dist.

Doug. County Surveyors Office - V. "Ray" Tracy; V. Perron
April 2, 1968 - C.S. File 54/7-70

Found - Remains of old scribed square post.
Orig. 36" now 44" Laurel, alive, North 17.2 ft., prev. opened & shows fragmentary scribe on decayed blaze. Open lower & find "BT" scribe. Rescribe "¼ S3 CS BT" below old blaze.
Orig. 8" now 24" Laurel, alive, S.65°W., 39.6 ft., we do not open. Rescribe "¼ S10 CS BT".
Set Brass cap at cor. mkd: County Surveyor's T 26 S R 3 W
Office S 3
1968 S 10
New BTs- 8" D.Fir N.12°W., 43.4 ft. mkd. "¼ S3 CS BT.
9" D.Fir S.19½°W., 25.1 ft. mkd. "¼ S10 CS BT.
Corner lies on spur, sloping SW - face measure on orig. BTs.
(6/19/68 - Set steel fence post alongside BC and uncovered brass cap)

Found OK, Eugene Bloom, July, 1985 - M 99-12
Found Ok, Herman Pieske, Jan. 21, 1994 - M118-33

Fd. & used on BLM dependent resurvey by Bryan Seibold, Cad. Surveyor & Robert Browning, Surveying Technician, under Group #1777 surveyed Aug/Sept 1995 - (DCSO rec Vol. 52 Pgs 19890-1)

FD. Ok by Carl Sweeden, 2/2006 - M149-57

Fd. 4 BTs as per 1968 dcso ren. - DCSO, John Pike & Stephen Flause - 3/3/2008 - C.S. File 67/25-29