

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 3

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

William Stiles - For: Ralph DeMoisy - Sept. 1968 & April 1970
- M 36-41 & M 36-41A

Set - 5/8" iron bar set.

AA Surveying, Herman Pieske - Jan. 21, 1994 - M118-33

Found - 5/8" IR per M36-41A bears S.76°53'34"E., 7.9 ft.
Set - 5/8"x 30" iron rod w/ plastic cap marked "AA
Surveying Inc."

New Accessories -

10" madrone, bears N.12°E., 13.1 ft., bark scribed
"C1/4 S3 BT."

8" black oak, bears S.85°W, 9.6 ft., scribed "C1/4
S3 BT."

BLM dependent resurvey by Bryan s. Seibold, Cadastral
Surveyor & Robert H. Browning, Surveying Technician, under
Group #1777, surveyed Aug./Sept. 1995 - (DCSO records Vol. 52
Page(s) 19891)

The center ¼ sec. cor. of sec. 3, established by Pieske, in
1994, recorded in the Douglas County Surveyors Office, M118-
33, and is accepted as the corner; monumented with a rebar,
5/8" diam., firmly set, projecting 4" above ground, with a
yellow plastic cap, 1½" diam., mkd. AA SURVEYING, from which
bearing trees mkd. by Pieske:

A madrone, 12" diam., bears N.8½°E., 19 lks., with scribe
marks C¼ S3 BT visible on open blaze.

A madrone, 9" diam., bears S.0½°W., 66 lks., with scribe
marks C¼ S3 BT visible on open blaze.

An oak, 6" diam., bears N.80¼°W., 15 lks., with scribe
marks C¼ S3 BT visible on open blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" diam., 24" in the
ground, directly over the rebar, with brass cap mkd.

T26S R3W

C ¼ S 3

1995

Deposit a white "DEEP-1" magnetic marker at base and drive
aluminum fence post alongside the stainless steel post.

The corner is located N.80°W., 0.10 chs. dist. of a barbed
wire fence extending N.55°W., & woven wire fence extending S.

continued next page

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 440640

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

From this point, a point established as the center 1/4 sec. cor. of sec. 3 by William C. Stiles, Registered Land Surveyor No. 432, in 1970, recorded in the Douglas County Surveyors Office map file M36-41A, bears S.83°31'31"E., 0.12 chs.; monumented with a rebar, 5/8" diam., firmly set, projecting 6" above ground. This point is rejected due to improper methods and is not utilized in this survey.

Fd. 1995 USBLM BC/IP & accessories, Kris DeGroot - 5/2007 - M 153-14