

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 460460

PRIMARY CORNER DESCRIPTION NE 1/16 Sec. 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Bureau of Land Management resurvey by Bishop & Rogers
Group #1207, Survey July/Sept. 1984 (DCSO records, Vol. 47
Page 17900)

Point for center E 1/16 sec. cor. of sec. 15, at the
intersection with the E & W center line of the NE¼ of sec. 15
Set an iron post, 28" long, 2½" dia., 24" in the ground, with
brass cap marked: NE 1/16
 S 15
 1984

from which
 A Fir, 7" dia., bears N.84°E., 13 lks., mkd:1/16 S15 BT.
 A Cedar, 4" dia., bears S.19½°W., 32 lks., mkd: X BT.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff
Lorsung- 2/15/2023 - C.S. File 67/55-42

Found - 3¼" BLM brass cap (properly mkd) on iron pipe up 1".
Burned, sawn 15"x3' D.Fir stump N.84°E., 8.5 ft.
 healed low blaze, add 3½" mag nail top center.
8" I.Cedar singed blaze S.19½°W., 21.1 ft, fully
 healed low blaze.

Note - Area burnt
 Monument on westerly edge of large bench running
 North & South
 Compass decl. 14½°E.

Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
N 174499.696 E 243441.028