

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 500260

PRIMARY CORNER DESCRIPTION N 1/16 Secs 26 & 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Ken Hoffine, Lone Rock Timber - Sept. 1995 - M122-80

Set - 5/8"x40" iron rod with alum. cap mkd: LONE ROCK TIMBER
NW1/16 1995" 0.5 ft above ground,
15" D.Fir bears N.6½°E., 20.5 ft, We scribe N1/16 S26
and tag tree.
9" D.Fir bears N.38°W., 45.4 ft. We scribe N1/16 S27 BT
and tag tree.
Corner lies approx. 35 ft north of rock road.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor
and Robert H Browning, Survey Tech, Under Group No. 2268,
Surveyed July/Nov. 2009 - DCS0 records Vol. 57 Page(s) 22703

The N 1/16 sec. cor. of secs. 26 and 27, established by
Hoffine, in 1995 and is accepted as the cor., monumented with
an iron rebar, 5/8" dia., firmly set, projecting 3" above the
ground, with aluminum cap mkd.
LONE ROCK TIMBER
N 1/16
S 27|S 26
1995
PLS 2291
from which bearing trees mkd. by Hoffine
A fir, 21" dia., bears N.6½°E., 20.4 ft., w/healed blaze
A fir, 19" dia., bears S.17½°E., 28.9 ft., w/healed blaze
Corner is located 52 ft. N. of a graveled road, 12 ft. wide,
bears N.54°W. and S.54°E.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff
Lorsung- 1/19/2022 (filed 11/23/2022) - C.S. File 67/55-9

Found - 2½" alum. cap on 5/8" iron rod, up 1".
Burned sawn 22"x6½' D.Fir stump N.6½°E., 20.9 ft.
(rec. 20.4 ft) healed blaze add 3½" mag nail
right side center.
Burned-sawn 21"x2½' D.Fir stump S.19°E., 29.3 ft.
(rec. S.17½°E., 28.9 ft.) blaze - scar. Add 3½"
mag nail top center.
17" D.Fir N.39½°W., 45.5 ft. healed single blaze, BT
tag reads S.38°E., 45.4 ft, add 3½" mag nail right
side center. Unrecorded.
Alum post 1.5 ft. North.
Note - Area burnt 9/2020
Corner is 52 ft. N of gravel rd, 12' wide bears
N.54°W. & S.54°E.
Lat 43°16'56.64"N Long: 123°01'47.86"W.