

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 & 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - L.L. Williams & A.R. Flint, Under Contract #151 dated May 23, 1871 (DCSO records, Vol. 10 Pg. 4377)

Set Laurel post to cor. , from which
A Laurel 13" dia., bears N.80°E., 50 lks. dist.
A Laurel 11" dia., bears S.60°E., 37 lks. dist.
A Laurel 12" dia., bears S.25°W., 20 lks. dist.
A Laurel 14" dia., bears N.75°W., 37 lks. dist.

Found and tied by Samuel C. Flint, June 19, 1882 Under Contract #454 (DCSO records, Vol. 10 Page 4388)

Bureau of Land Management Resurvey by Berry; Popken; and Carlson, Under Group #768 Survey, June 1972-April 1975 (DCSO records, Vol. 37 Page 15398)

Point for the cor., at proportionate distance; there is no remaining evidence of the original corner.
Set and iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

T 26 S R 3 W
S 22 | S 23
S 27 | S 26
1972

from which
A Fir 13" dia., bears N.52°E., 131 lks. mkd. T26S R3W S23 BT.
A Fir 8" dia. bears S.30°E., 23 lks. mkd T26S R3W S26 BT
A Fir 16" dia. bears S.85°W., 93 lks mkd T26S R3W S27 BT
A Fir 6" dia., bears N.61°W., 27 lks mkd T26S R3W S22 BT

Found OK, Oct. 1995 by Hoffine - M122-80

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2268, Surveyed July/Nov. 2009 - DCSO records Vol. 57 Page(s) 22704

The cor. of secs. 22, 23, 26, and 27, monumented with an iron post, 2½" dia., firmly set, projecting 11" above the ground, with brass cap (properly) mkd.
from which BTs mkd. by Berry, Popken, and Carlson in 1972-75
A fir, 25" dia., bears N.47¼°E., 86.5 ft., with a healed blaze. (Record, N.52°E.)
A fir, 23" dia., bears S.30°E., 15.2 ft w/a healed blaze
A fir, 26" dia., bears S.85°W., 61.4 ft w/a healed blaze
A fir, 19" dia., bears N.61°W., 17.8 ft w/a healed blaze

continued next page

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 1/20/2022 (Filed 4/12/2022) - C.S. File 67/52-7

Found - 3¼" BLM brass cap on 2" I.D. iron pipe projecting 8" Down, burnt 27" D.Fir N.47¼°E. 86.5 ft to root hole. Burnt sawn 20"x7 ft. Fir stump N.53°W., 17.8 ft. with healed single blaze.
New - Burnt 20" D.Fir N.35°E., 27.5 ft. to 4" mag nail RT side center, no blaze or scribe.
27" burnt Maple S.35°W., 23.0 ft. no blaze or scribe
4" mag nail RT side center.
Note - Area burnt 9/2020
See sketch in file
Compass decl. 14½°E.
Lat: 43°17'09.75" N Long: 123°01'47.87" W