

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W. H. Byars, Under Contract #269 dated July 24, 1877 (DCSO records, Vol. 10 Page 4379)

Marked a white fir, 5" dia., for the cor., from which
A Red Fir 16" dia., bears N.72°E., 23 lks. dist.
A Maple, 10" dia., bears S.77°E., 19 lks. dist.
A W.Fir 6" dia., bears S.72°W., 11 lks. dist.
A Red Fir 30" dia., bears N.46°W., 25 lks. dist.

Found and used, S.C. Flint, Cadastral Surveyor, Contract #454 dated June 19, 1882 (DCSO records, Vol. 10 Page 4392)

G.G. Stewart, Deputy Co. Surveyor Witn: Max Shellabarger;
M.L. Kimmel - Marcy 18, 1922 - Vol. 3 Page 114

Renew from on O.B.T. standing and 2 rotten. Set 1" Galv. I.P. with yew marker. Marked:
Fir 36" N.46°W., 16.5 ft.
Fir 30" N.30°E., 21.7 ft.
Fir 24" S.58°E., 42.7 ft.
Yew 10" S.41°W., 19.0 ft.

Bureau of Land of Management resurvey by White, Beck & Reynolds, Group #'s 242, 491 & 527, Survey June 1962-Aug 1963 - (DCSO records, Vol. 32 Page 13381)

The cor. of secs. 10, 11, 14 and 15, perpetuated and recorded by G.G. Stewart, in 1922, monumented with an I.P. 1" dia., firmly set, protruding 1" above the ground, from which the remains of the original bearing trees:
A rotted Fir stump shell, 18" dia., bears N.70°E., 23 lks. dist., (Record bearing N.72°E.)
A Fir 23" dia., bears S.72°W., 11 lks. dist., with old scars and rotted center.
A Fir 40" dia., bears N.46°W., 27½ lks. dist., (25 lks. to face) with scribe marks T26 R3 S10 BT on recent bark blaze. (Rec. dist. 25 lks.)
and the county surveyor's bearing trees:
A Fir snag 33" dia., bears N.32°E., 33 lks. dist., with various old scars.
A Fir 34" dia., bears S.58°E., 66 lks. dist., with scribe marks CS S14 BT on bark blaze.
A Yew 13" dia., bears S.41°W., 29 lks. dist., with fragmentary scribe marks on partially healed blaze.

At the corner point

continued next page

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Sec Cor for 10, 11, 14 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

T 26 S R 3 W
S 10 | S 11
S 15 | S 14
1962

from which a new bearing tree

A Cedar 21" dia., bears N.47°E., 110. lks. dist., mkd.
T26S R3W S11 BT.

Reset the County Surveyors I.P. inside the Iron post.

Found and used, BLM resurvey by Bishop and Rogers, July 1984 Group #1207 - DCS0 records, Vol. 47 Pages 17895-96)

Dependent resurvey by Jeffrey O Covington, cadastral Surveyor under Group 2953, Surveyed Sept/Oct 2019 (DCS0 Records Vol. 59 Pages 23986-23988 and Plat maps T26-3 2021-1 thru 2021-3)

The cor. of secs. 10, 11, 14, and 15, reported by Bishop and Rogers in 1984, monumented with an iron post, 2½" dia., firmly set, projecting 2" above ground, with a brass cap (properly) mkd.

from which the remains of the BTs reported by Bishop & Rogers
A decayed fir stump, 33" dia., bears N.32°E., 21.8 ft., no marks visible.

A cedar, 33" dia., bears N.47°E., 72.6 ft., with a healed blaze.

A fir, 38" dia., bears S.58°E , 43.6 ft., with scribe marks S14 BT visible on bark.

A decayed yew stump, 18" dia., bears S.41°W., 19.1 ft., alongside of which is a down yew trunk, 18" dia., with no marks visible on hollowed blaze.

A fir, 35" dia., bears S.72°W., 7.3 ft., no marks visible.
(Original)

A fir stump, 41" dia., bears N.46°W., 18.2 ft. with axe marks visible on bark. (Original)

and a bearing tree mkd. by person(s) unknown

A fir, 12" dia., bears N.9¼°E, 25.1 ft with a healed blaze and a new bearing tree

A fir, 13" dia, bears N.23°W., 37.4 ft mkd T26S R3W S10 BT
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.

Latitude 43°18'55.43"N Longitude 123°01'49.10"W
NAD 1983 (2011)