


TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 540120

PRIMARY CORNER DESCRIPTION CS 1/16 S 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original BLM survey by Wayne L. Rogers, Cadastral Surveyor, surveyed April 15, 1981(D.C.S.O. records, Volume 45 Pgs. 17439-17440)

Set - Iron post 28" long, 2½" diam. 24" in ground with brass cap mkd.




Notes - 28" Fir bears N.32°E. 8½ lks. mkd C S 1/16 S35 BT
25" Fir bears N.56½°W. 29 lks. mkd C S 1/16 S35 BT
Ascend 40' over S.W. slope, there is an 18" Fir that bears S.46°E. 8 lks with illegible scribe marks visible on partially healed blaze.

The corner is located in the S.W. corner of a logged area.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flauser and Jeff Lorsung - 9/30/2025 - C.S. File 67/61-30

Found - ¾" BLM brass cap, proj. 3"



Sawn, rotted 23" x3 ft. fir stump. N.32°E. 6.0 ft. (Rec. 8½ lks.) to ¾" mag nail right side center. Illegible scribes on unhealed single blaze.

Sawn, burnt 25" x2½ ft. D.fir stump N.56½°W. 19.0 ft. (Rec 29 lks) to ¾" mag nail right side center. All scribes visible on unhealed single blaze.

Both BT's have galv. steel caps.

Notes - Area burnt 9/2020.

Compass decl. 14¼°E.

OGRS COORDINATE SYSTEM

COTTAGE GROVE-CANYONVILLE ZONE

43°15'37.99150" N.

123°01'11.80653" W.