

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Section 26

Alias	Description

Bureau of Land Management Subdivision of Section by Popken; Berry and Carlson, Under Group # 768 - Survey, June 1972-April, 1975 (DCSO Records, Vol. 37 Page 15406)

Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E. and W. center line.

Set an iron post, 28" long 2½ ins. dia., 22" in the ground, with brass cap mkd.

T 26 S R 3 W
C 1/4 S 26
1972

from which

A Maple 6" dia., bears N.19°E., 16 lks. mkd. C ¼ S26 BT.

A Fir 8" dia., bears S.8°E., 29 lks., mkd. C ¼ S26 BT.

Corner is located in ravine, drains W.

Mark Smalley - For: Roseburg Resources - 8/2003 - C.S. File 65/48-14

Found - 1972 BLM IPBC (properly mkd)

14" Maple N.33°E., 8.4 (tag S.19°E., 10.6) healed.

25" Fir S.4°E., 21.7 (tag S.8°E., 18.5, rec. 19.1) healed.

New - 17" Fir, S.18°W., 15.3, scribed "C¼ BT"

10" Maple, N.74°W., 48.4, scribed "C¼ BT"

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2268, Surveyed July/Nov. 2009 - DCSO records Vol. 57 Page(s) 22709

The center ¼ sec. cor. of sec. 26, perpetuated by Smalley, in 2003, monumented with an iron post, 2½" dia., firmly set, projecting 7" above the ground, with brass cap (properly) mkd.

from which BTs mkd. by Berry, Popken, and Carlson in 1972-75

A maple, 13" dia., bears N.28¼°E., 8.3 ft., with a healed blaze. (Record, N.19°E., 10.6 ft.)

A fir, 28" dia., bears S.3½°E., 21.2 ft., with a healed blaze. (Record, S.8°E., 19.1 ft.)

and bearing trees mkd. by Smalley

A fir, 20" dia., bears S.20¾°W., 15.1 ft., with a healed blaze.

A maple, 10" dia., bears N.70½°W., 48.1 ft., with scribe marks C¼ BT visible on a partially healed blaze.

Corner is located 47 ft. S. of a creek, 2 ft. wide, course S.70°W.