

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 14 & 23

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Samuel C. Flint, Under Contract #454, dated  
June 19, 1882 - (DCSO records, Vol. 11 Pg 4394)

-----  
Set Cedar post, 3 ft. long 4" sq., firmly in the ground  
mkd. 1/4 S on N. and S. faces, from which

A Fir 18" dia., bears S.20°E., 18 lks. dist. mkd.  
1/4 S BT.

A Fir 30" dia., bears N.60°W., 27 lks. dist. mkd.  
1/4 S BT.

-----  
Harley E. Case & John Wilson, For: Weyerhaeuser Co.  
May 1966 - C.S. File 55/19-2

-----  
Did not find original GLO record.

Set 1" alum. pipe by single proportionate method.

Referenced by Glen McChesney (plates & "W" nails only)

BTs - 52" Fir N.28°E., 20.4 ft.

24" I.Cedar S.35°W., 21.6 ft.