

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 560120

PRIMARY CORNER DESCRIPTION S E 1/16, S 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Bureau of Land Management survey by Wayne L. Rogers under Group #1058 - Survey, June/Aug. 1981 (DCSO records, Volume 45 Page 17443)

Point for the SE 1/16 sec. cor. of sec. 35, at intersection with the E. and W. center line of the SE 1/4.
Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap mkd.
SE 1/16
S 35
1981

from which
A fir, 26" dia. bears N.70°E., 48½ lks. mkd SE 1/16 S35 BT
A cedar, 19" dia. bears N.55°W. 16 lks mkd. SE 1/16 S35 BT

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 9/25/2025 - C.S. File 67/61-28

Found - BLM 3¼" brass cap on iron post. proj 6"
39" fir, N.68°E. 32.0 ft. (Rec N.70°E. 48½ lks.)
Down 28" cedar. N.55°W. 10.6 ft. (Rec 16 lks.) to root hole.
SE 1/16
S 35
1981

New - 6" W. fir. S.52°E. 3.0 ft. scribed "X" CS BT on high-low blaze.

Notes - Area burnt 9/2020
Compass decl. 14¼°E.
TRIMBLE GEO XT POSITION
43°15'38.073" N.
123°00'53.748" W.