

TOWNSHIP 26 RANGE 3 POINT IDENTIFIER # 560140

PRIMARY CORNER DESCRIPTION C.E. 1/16 S35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original BLM survey by Wayne L. Rogers, Cadastral Surveyor, surveyed April 15, 1981(D.C.S.O. records, Volume 45 Pgs. 17441)

Set - Iron post 28" long, 2½" diam, 22" in ground with brass cap mkd.

C E 1/16 C
S 35
1981

12" Grand Fir bears N.19½°E. 11½ lks, mkd. CE 1/16 S35 BT.

14" Yew bears S.16½°E. 40½ lks. mkd CE 1/16 S35 BT.

Notes - Ascend 5ft over N.E. slope. Spur, slopes N.10°E.; desc, 400 ft. over N.W. slope.

Gravelled road 25 lks wide bears N.25°E. and S.25°W.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flauser and Jeff Lorsung - 9/30/25 - C.S. File 67/61-31

Found - ¾" BLM brass cap, proj. 8" in rough mound of stone.

C E 1/16 C
S 35
1981

Very burnt 15" x 25' grand fir snag. N.19½°E. 7.6' fully healed single blaze. Add ¾" mag nail right side center.

Very burnt down 11" yew. S.16½°E. 26.7' to root hole. Burnt out blaze.

New - 13" W.Fir, dead burnt base. East 2.6'. ¾" mag nail, right side center.

Compass decl. 14¼°E.

OCRS COORDINATE SYSTEM

COTTAGE GROVE-CANYONVILLE ZONE

43°15'51.01923" N.

123°00'53.96022" W.