

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - L.L. Williams and A.R. Flint, Under Contract #151 dated May 23, 1871 (DCSO records, Volume 10 Pages 4375-76)

Set post to cor. of secs. 25, 26, 35 and 36 from which,
A fir 12" dia., bears N.50°E., 6 lks. dist.
A Fir 12" dia., bears S.30°E., 11 lks. dist.
A Fir 20" dia., bears S.35°W., 20 lks. dist.
A Fir 20" dia., bears N.30°W., 32 lks. dist.

GL0 survey by Samuel C. Flint, Under Contract #454 dated June 19, 1882 (DCSO records, Volume 10 Pages 4384-85)

Survey commenced July 6, 1882.
Found - Cedar post, 4 ft. long, 4" sq. firmly set in the ground, and marked T26S Sec. 25 on NE., R3W Sec. 36 on SE., S35 on SW and S26 on NW faces, with 1 notch on S & E edges.
A Fir 12" dia., bears N.50°E., 6 lks. dist., mkd. T26S R3W S25 BT.
A Fir 20" dia., bears N.30°W., 32 lks. dist. mkd. S 26 BT.
A Fir 20" dia., bears S.35°W., 20 lks. dist., mkd. S 35 BT.
A Fir 12" dia., bears S.30°E., 11 lks. dist. mkd. S 36 BT.

Thomas E. Shrum, Jr. For: U.S. Plywood - November 1962 - C.S. File 51/254-1

Found - 25" D.Fir S.46°W., 9.8 ft.
36" D.Fir stump N.23°W., 25.5 ft.
Set - 2½" Aluminum cap.
New BTs - 10" Maple S.74°E., 46.2 ft. mkd. S36 BT.
18" Cedar N.78½°W., 31.0 ft. mkd. S26 BT.
8" Yew N.52°E., 31.2 ft. mkd. S25 BT.

Doug. County Surveyors Office - Vernon Tracy; Mike Stone; Jack Heritage - Jan/Feb. 1966 - C.S. File 54/7-17

Found - Orig. 20" now 25" Fir S.35°W., 13.2 ft. Alive, prev. opened & shows "S" scribe.
(Cont. Next Page)

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Orig. 20" now 36" Fir stump N.30°W., 21.1 ft., find fragmentary bark scribe.
¾" I.Pipe & alum. cap, as recorded by Shrum which bears S.10°W., 4.3 ft. from true corner location. Believe Mr. Shrum had wrong notes in the field.

Set - Brass cap at cor. mkd. County Surveyors T26S R3W
Office, 1966 S26|S25
S35|S36

New bearings and distances to Shrum's BTs:
10" Maple S.70½°E., 46.3 ft. mkd. "S36 BT" & alum. tag "RE 4287".
8" Yew N.57°E., 27.7 ft. mkd. "S25 BT" & alum. tag RE 4287.
18" Cedar N.85°W., 30.0 ft. mkd. S26 BT" & Alum. tag RE 4287.
Use orig. BT to SW.

Fd. OK, BLM resurvey by Berry; Popken; & Carlson, under Group #768 June 1972-April 1975 (DCSO records, Vol. 37 Pg. 15392)

Fd. OK, BLM resurvey by Wayne L. Rogers, Under Group #1058 June/Aug. 1981 (DCSO Records, Vol. 45 Pages 17435-36)

Fd. Ok by M. Smalley, Aug. 2003, C.S. File 65/48-16

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause - 12/5/2007 - C.S. File 67/24-49

Found ok, 4 live BTs as per 1966 DCSO renewal. Shrum's ¾" IP/Alum cap not found.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2268, Surveyed July/Nov. 2009 - DCSO records Vol. 57 Page(s) 22695

The cor. of secs. 25, 26, 35, & 36, monumented with an iron post, 1¼" dia., firmly set, projecting 15" above the ground, with brass cap (properly) mkd.
from which the remains of the original bearing trees
A fir, 35" dia., bears S.32°W., 13.2 ft., with a healed blaze.
A sawed fir stump, 43" dia., bears N.30°W., 21.1 ft., with a healed blaze.
and BTs mkd. by Shrum, in 1962

continued next page

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A yew, 9" dia., bears N.57°E., 27.1 ft., with scribe marks S25 BT visible on a partially healed double blaze.

A maple, 15" dia., bears S.71°E., 46.2 ft., with a healed double blaze.

A cedar, 28" dia., bears N.85°W., 30.4 ft., with a healed double blaze.

The corner of sections 25, 26, 35, and 36:

Latitude: 43°16'17.52"N. Longitude: 123°00'35.72"W.
(NAD 1983 (CORS))

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 12/1/2021 (Filed 4/7/2022) - C.S. File 67/51-36

Found - DCS0 Brass cap with steel lath, 1 ft. East.
(properly mkd)

Shrubs 62 mon removed by logging, not fd.

Singed 38" Fir S.32°W., 12.9 ft.(rec. 13.2 ft)
healed blaze.

Burned 24"x3 ft. sawed Fir stump N.30°W., 21.1 ft.,
healed blaze, nail left side center.

10" Yew N.57°E., 27.8 ft. healed double blaze.

16" maple S.71°E., 46.2 ft. healed double blaze.

30" Cedar N.85°W., 30.4 ft. healed double blaze.

BTs have nails right side center.

Note - See sketch in file

Compass decl. 14½°E.

Lat: 43°16'17.57" N Long: 123°00'35.77" W
(See C.S. 67/51-36 Pg 3/13)