

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Samuel C. Flint, Under Contract #454 dated June 19, 1882 (DCSO records, Vol. 10 Page 4386)

Set post, 3 ft. long, 3" sq., firmly set in the ground, for 1/4 sec. cor. mkd. on E and W faces 1/4 S, from which

A Fir 6" dia., bears N.15°W., 15 lks. dist., mkd. 1/4 S BT.

A Fir 6" dia., bears N.18°E., 18 lks. dist., mkd. 1/4 S BT.

Bureau of Land Management resurvey by Berry; Popken; and Carlson, Under Group #768 - Survey June 1972-April 1975 (DCSO records, Vol. 37 Pg. 15392)

Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd. T 26 S R 3 W

1/4
S 26 | S 25
1972

from which

A Fir 20" dia., bears N.51°E., 26 lks., mkd. 1/4 S25 BT.

A Fir 15" dia., bears N.69°W., 25 lks., mkd. 1/4 S26 BT.

Mark Smalley - For: Roseburg Resources - 8/2003 - C.S. File 65/48-17

Found - 1972 BLM IPBC (properly mkd)
22" Fir N.69°W., 16.5 healed.
28" Fir N.51°E., 17.2 healed.

New - 9" Fir S.6°E., 14.6, scribed "1/4 S BT"
7" Fir S.41°W., 19.6 scribed "1/4 S BT"