

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Samuel C. Flint, Under Contract #454 dated June 19, 1882 - (DCSO records, Vol. 10 Page 4386)

-----  
Set Cedar post, 4 ft. long, 4" sq., firmly in the ground for cor., mkd. T26S S24 on NE., R3W S25 SE., S26 SW and S23 NW., with 2 notches on the S and 1 notch on the E from which

- A Cedar 12" dia., bears S.8°E., 10 lks. dist., mkd. T26S R3W S25 BT.
- An Alder 6" dia., bears N.10°E., 30 lks. dist., mkd T26S R3W S24 BT.
- A Cedar 12" dia., bears N.45°W., 20 lks. dist., mkd. T26S R3W S23 BT.
- A Cedar 12" dia., bears S.70°W., 38 lks. dist., mkd. T26S R3W S26 BT.

Bureau of Land Management resurvey by Popken; Berry and Carlson - Under Group #768 - Survey, June 1972-April 1975 (DCSO records, Vol. 37 Page 15393)

-----  
Point for the cor., at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. T 26 S R 3 W  
S 23 | S 24  
S 26 | S 25  
1972

from which

- A Fir 50" dia., bears N.31°E., 13 lks. dist., mkd. T26S R3W S24 BT.
- A Hemlock 14" dia., bears S.47°E., 22 lks. dist., mkd. T26S R3W S25 BT.
- A Hemlock, 13" dia., bears S.11°W., 48 lks. dist., mkd. T26S R3W S26 BT.
- A Hemlock 6" dia., bears N.40°W., 25 lks. dist., mkd. T26S R3W S23 BT.

Ronald Geisler, For: Champion International - Wit: L. Sibley; D.Turner - Jan. 31, 1984 - C.S. File 58/146-3

-----  
Found - 1972 BLM brass cap (properly marked)  
50" Fir bears N.31°E., 8.6 ft. with healed face.  
17" Hemlock bears S.47°E., 14.5 ft. w/ healed face.  
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias	Description
Alias	Description
Alias	Description
Alias	Description

16" Hemlock bears S.11°W., 31.1 ft. with scribing partially visible.  
6" Hemlock stump 2 ft. tall bears N.40°W., 16.0 ft. scribed "T26S R3W S23 BT".  
New BT - 13" hemlock bears N.13°W., 18.9 ft. scribed T26S R3W S23 BT.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2268, Surveyed July/Nov. 2009 - DCSO records Vol. 57 Page(s) 22696  
-----  
The cor. of secs. 23, 24, 25, and 26, monumented with an iron post, 2½" dia., firmly set, projecting 5" above the ground, with brass cap (properly) mkd. from which the remains of bearing trees mkd. by Berry, Carlson, and Popken in 1972-75  
A fir, 59" dia., bears N.31°E., 8.6 ft., with a healed blaze.  
A hemlock, 22" dia., bears S.47°E., 14.5 ft., with a healed blaze.  
A hemlock, 20" dia., bears S.11°W., 31.7 ft., with a healed blaze.  
A roothole bears N.40°W., 16.5 ft., alongside of which is a fallen, decayed hemlock trunk, size indeterminate, with scribe marks T26S R3W S visible on a wood fragment.  
and a bearing tree mkd. by Ronald G. Geisler  
A hemlock, 16" dia., bears N.14°W., 19.0 ft., with a healed double blaze.