

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Samuel C. Flint, Under Contract #454, dated June 19, 1882 (DCSO records, Volume 10 Page 4389)

-----  
Set Cedar post, 3 ft. long, 3" sq., firmly in the ground marked on E and W faces ¼ S; from which  
A Fir 36" dia., bears N.60°W., 32 lks., mkd. ¼ S BT  
A Cedar 14" dia., bears S.85°E., 25 lks., mkd. ¼ S BT.

Weyerhaeuser Timber Company & Youngs Bay Lumber by: Lester E. Calder, Wit: Glen McChesney; Tom Shrum; Don Wright  
April 1960 - C.S. File 51/87-2

-----  
Found - No trace, 36" Fir N.60°W., 32 lks.,  
14" Cedar S.85°E., 25 lks., faint scribe marks.  
Found stake found by 1950-51 survey. Referenced by G. Mcchesney, (plates and "W" nails only)  
42" Fir stump N.83°W., 37.7 ft.  
36" I.Cedar S.85°E., 15.4 ft. (Orig.)

Doug. County Surveyors Office - Vernon Tracy; Mike Darby; Terry Connell Wit: Glen McChesney, Weyerhaeuser Co. - June 8, 1965 - C.S. File 54/7-35

-----  
Found - 14" now 37" I.Cedar stump S.85°E., 16.5 ft., chopped out, face rotted, very faint scribe visible. Stump 6.0 ft. high.  
42" Fir stump N.83°W., 37.7 ft. to "W" nail, no scribe.

Set Brass cap at cor. mkd: County Surveyors Office, 1965  
T26S R3W ¼ S23|S34

New BT - 14" I.Cedar N.77°E., 45.1 ft. mkd. ¼ S24 CS BT.  
No other trees available.

This corner lies on top of rounded hill, rolling off to North.

Bureau of Land Management resurvey by Popken; Berry; and Carlson Under Group #768 - Survey June 1972-April 1975 (DCSO records, Vol. 37 Pages 15394-95)

-----  
Found the ¼ sec. cor. of secs. 23 and 24, perpetuated and recorded by Vernon Tracy in 1965, monumented with & iron post, 2" dia., firmly set, protruding 10" above ground with brass cap properly marked.  
from which the remains of the original bearing tree continued next page

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs 23 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Cedar stump 35" dia., bears S.85°E., 25 lks. with fragmentary scribe mks visible on decayed opened blaze and a bearing tree marked by Tracy  
A Cedar 18" dia., bears N.76°E., 68 lks. with scribe marks ¼ S24 CS BT visible on partially healed double blaze. and a new bearing tree  
A Fir 6" dia., bears S.47°W., 21 lks. mkd. 1/4 S23 BT.

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause - 12/4/2007 - C.S. File 67/24-48  
-----  
Found ok; orig. cedar stump, 1065 I.Cedar renewal tree as per 1972 BLM report.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2268, Surveyed July/Nov. 2009 - DCS0 records Vol. 57 Page(s) 22698  
-----  
The ¼ sec. cor. of secs. 23 and 24, monumented with an iron post, 1¼" dia., firmly set, projecting 8" above the ground, with brass cap (properly) mkd. from which the remains of an original bearing tree  
A decayed cedar stump, 31" dia., bears S.85°E., 16.5 ft., with axe marks visible.  
and the remains of a BT mkd. by Lester E. Calder, in 1960  
A sawed, decayed fir stump, 48" dia., bears N.81¼°W., 40.7 ft., with no marks visible.  
and a bearing tree mkd. by Tracy, in 1965  
A cedar, 29" dia., bears N.76°E., 44.9 ft., with a healed blaze.  
and the remains of a BT mkd. by Berry, Popken, and Carlson  
A fir snag, 20" dia., bears S.47°W., 13.9 ft., with a healed blaze.  
and a new bearing tree  
A fir, 17" dia., bears N.6°W., 32.7 ft., mkd. ¼ S23 BT.

Fd as per 2009 BLM resurvey by D. Edwards, 10/2012 - M164-32

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 1/25/2022 (Filed 4/13/2022) - C.S. File 67/52-10  
-----  
Found - 2½" DCS0 brass cap, projecting 8" above ground, properly marked.  
Sawn 26"x2' cedar stump N.76°E., 44.9 ft.  
A down burnt 20" Fir S.47°E., 13.9 ft. to burned out crown.  
23" D.Fir N.6°W., 33.2 ft. to PK nail RT side center (Rec. 32.7 ft) partially healed single blaze.  
Continued next page

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Sawn 16"x1 ft tall Hemlock stump N.69°W., 34.9 ft.  
4" mag nail, top center.  
24" D.Fir S.23°W., 50.5 ft. mag nail RT side center.  
Not blazed or scribed.  
A burnt 26" Hemlock N.80°W., 30.0 ft. to mag nail RT  
side center. No blaze or Scribe.

Note - Area Burnt 9/2020  
Compass decl. 14½°E.  
See sketch in file.

Lat: 43°17'35.31" N Long: 123°00'36.07" W