

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 600360

PRIMARY CORNER DESCRIPTION N. 1/16 Cor. for Secs. 23 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Lester E. Calder - For: Weyerhaeuser - C.S.49/46 - 1950/51 ----- Set- 2" Cedar Post by single proportionate method. Referenced by Curtis Price (Weyerhaeuser Method): 18" Fir S.89°E., 31.1' 18" Fir N.24°E., 36.3' This information added to the corner report on 9/26/2001. DCS0</p>
<p>Weyerhaeuser corner report, Glen McChesney - C.S. File 51/87-2 & C.S. File 53/115 - Aug. 18, 1959 ----- Found post 20" Fir stump S.88°E., 31.1 - WTC0 Young Bay OBT, "W" nail, plate, brass disk. 20" Fir N.21°E., 36.3 - WTC0 Young Bay OBT, "W" nail, plate, brass disk. This information added to the corner report on 9/26/2001. DCS0</p>
<p>Mike Juliano, for Weyerhaeuser Timber Company - Sept. 1973 C.S. File 55/316 ----- Corner set by proportionate measurement. Set 2½" Iron pipe with brass cap BTs - 16" Maple S.42°W., 41.4 ft. to "W" nail. 22" Fir N.76°E., 44.4 ft. to RR Spike.</p>
<p>BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2268, Surveyed July/Nov. 2009 - DCS0 records Vol. 57 Page(s) 22699 ----- The N1/16 sec. cor. of secs. 23 & 24, established by Juliano, in 1973, and is accepted as the cor., monumented with an iron post, 2½" dia., firmly set, projecting 7" above the ground, with brass cap (properly) mkd. from which the remains of bearing trees mkd. by Juliano A sawed fir stump, 35" dia., bears N.75¼°E., 45.9 ft., with no marks visible, and a railroad spike driven into the face. A maple, 22" dia., bears S.41¾°W., 42.5 ft., with a healed blaze. and a new bearing tree A cedar, 17" dia., bears S.50¼°E., 12.2 ft., mkd. N 1/16 S24 BT.</p>
<p>1</p>