

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Samuel C. Flint, Under Contract #454 dated June 19, 1882 (DCSO records, Vol. 10 page 4389)

Set a fir post, 4 ft. long, 4" sq., firmly in the ground, for cor. marked T26S S13 NE., R3W S24 on SE., S23 on SW and S14 on NW faces, with 3 notches on the S and 1 notch on the E edges, from which

- A Cedar 30" dia., bears N.70°E., 58 lks. mkd. T26S R3W S13 BT.
- A Cedar 30" dia., bears S.82°E., 19 lks. mkd. T26S R3W S24 BT.
- A Cedar 12" dia., bears S.78°W., 85 lks. mkd. T26S R3W S23 BT.
- A Cedar 24" dia., bears N.17°W., 170 lks. mkd. T26S R3W S14 BT.

Lester E. Calder, For: Weyerhaeuser Timber Co., Oct. 1, 1952
C.S. File 41/76

Found - The 30" Cedar BT S.82°E., 19 lks in good condition. Short shells of burned out Cedars were found in the approx. position for the NE and NW Cedar BTs. A fire evidently destroyed the SW BT after it was knocked down by a large snag.

Set a 2½" square Cedar post, S.82°E., 19 lks. from the identified 30" Cedar BT.

Referenced four trees by nailing a 4.7 x 5.7 inch alum. plate with embossed section plat nailed head high on trees. Near base of tree a notch is cut & a square headed nail with W on head driven through a hole in a 2½" brass disc stamped with the Surveyors of Engineers Reg. number.

- 28" Cedar S.36°E., 37.5 ft.
- 32" Fir N.65°E., 40.4 ft.
- 14" Fir N.84°W., 31.6 ft.
- 24" Fir S.22°W., 57.5 ft.

Found OK, Corner report, Weyerhaeuser Co. and Youngs Bay Lumber - April 1960, C.S. File 51/87-2

Doug. County Surveyors Office - Vernon Tracy; Mike Darby; Terry Connell and Glen McChesney of Weyerhaeuser Co.
June 1965 - C.S. File 54/7-34 - (WEYCO C.S. 53/115-12&17)

Found - Remains of 3 original BTs and BTs recorded by Weyerhaeuser Co. BTs in good condition

(Cont. Next Page)

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set Brass cap at cor. mkd: County Surveyors S 14|S 13 T26S
Office, 1965 S 23|S 24 R3W
New BTs- 13" hemlock N.10°E., 10.0 ft mkd. T26S R3W S13 CSBT
10" D.Fir N.24°W., 34.6 ft. mkd. T26S R3W S14 CS BT
18" Fir N.87°W., 31.0 ft. mkd. T26S R3W S14 CS BT.
28" Cedar S.40°E., 39.1 ft. mkd. T26S R3W S24 CS BT
This cor. lies 17.0 ft. west of small creek flowing
northerly.

(See C.S. File 55/19-1& 2 for listing of Weyerhaeuser trees)
(See also C.S. File 55/316 for Mike Juliano's Sept. 1973
report of the same trees listed in 1952 Weyerhaeuser survey

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause
- 12/4/2007 - C.S. File 67/24-48

Found OK; 3 live BTs as follows:
From 1952 ren: 32" Fir N.65°E., 37.5 ft.
24" Fir, S.22°W., 57.5 ft.
From 1965 ren: 13" hemlock N.10°E., 10.0 ft.
Also 2 sturdy stump.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor
and Robert H Browning, Survey Tech, Under Group No. 2268,
Surveyed July/Nov. 2009 - DCS0 records Vol. 57 Page(s) 22700

The cor. of secs. 13, 14, 23, & 24, perpetuated by Calder, in
1952, further perpetuated by Tracy, in 1965, monumented with
an iron post, 1¼" dia., firmly set, projecting 7" above the
ground, with brass cap (properly) mkd.
from which the remains of the original bearing trees
A roothole bears N.70°E., 38.3 ft., alongside of which
is a cedar trunk, 15" dia., with no marks visible.
A broken, decayed cedar stump, size indeterminate, bears
S.82°E., 12.5 ft., alongside of which is a cedar
trunk, 35" dia., with axe marks visible.
and bearing trees mkd by Calder
A fir, 48" dia., bears N.63½°E., 41.4 ft., with a healed
blaze.
A fir, 40" dia., bears S.21°W., 57.9 ft., with no marks
visible.
and bearing trees mkd. by Tracy
A hemlock, 25" dia., bears N.12½°E., 9.8 ft., with a
healed double blaze.
A sawed, decayed cedar stump, 24" dia., bears S.40°E.,
39.3 ft., with no marks visible. cont.

PRIMARY CORNER DESCRIPTION Sec Cor for 13, 14, 23, & 24

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

A sawed fir stump, 27" dia., bears N.87°W., 31.0 ft., with a healed double blaze.
and a new bearing tree
A hemlock, 12" dia., bears S.26½°E., 44.3 ft., mkd. T26S R3W S24 BT.

Dependent resurvey by Jeffrey O Covington, cadastral Surveyor under Group 2953, Surveyed Sept/Oct 2019 (DCSO Records Vol. 59 Pages 23986-23988 and Plat maps T26-3 2021-1 thru 2021-3)

The cor of secs. 13, 14, 23, & 24 perpetuated by Douglas Co. Surveyor's Office, in 1965; reported by Skeesick & Browning in 2009; monumented with an iron post, 1¼" dia., firmly set, projecting 7" above ground, with a brass cap (properly) mkd. from which the remains of a bearing tree mkd. by the Douglas County Surveyor's Office in 1965
A roothole bears N.25°W., 31.2 ft., alongside of which is a down decayed fir trunk, 16" dia., with illegible scribe marks visible on partially healed blaze.
and the remains of the BTs reported by Skeesick and Browning
A hemlock, 26" dia., bears N.12½°E., 9.8 ft, with a healed double blaze.
A fir, 48" dia., bears N.63½°E 41.4 ft., no marks visible.
A broken, decayed cedar stump, size indeterminate, bears S.82°E., 12.5 ft., alongside of which is a down, decayed cedar trunk, 35" dia., with axe marks visible on bark. (Original)
A decayed cedar stump, 23" dia., bears S.40°E., 39.3 ft., no marks visible.
A roothole bears S.26½°E., 44.3 ft., alongside of which is a down hemlock trunk, 14" dia., with scribe marks T26S R3W S24 BT visible on partially healed blaze.
A fir, 42" dia., bears S.21°W., 57.9 ft., with a healed blaze.
A decayed fir stump, 26" dia., bears N.87°W., 31.0 ft., with a healed blaze.
and new bearing trees
A hemlock, 10" dia., bears S.56°E , 56.4 ft., mkd. T26S R3W S24 BT.
A hemlock, 16" dia., bears N.66¼°W., 24.3 ft., mkd. T26S R3W S14 BT.
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.
Corner is located W., 20 ft. of creek, 2 ft. wide, course N.30°E.
Lat: 43°18'01.34"N Long: 123°00'34.90"W NAD 1983 (2011)