

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W. H. Byars, Contract #317 dated Jan. 20, 1879
(DCSO records, Vol. 10 Page 4382)

Set fir post, 5 ft. long, 20" in ground, 5" dia., from which
A Fir 20" dia., bears N.48°E., 58 lks. dist.
An Oak 10" dia., bears S.88°E., 180 lks. dist.
A Fir 20" dia., bears S.88°W., 66 lks. dist.
A Fir 60" dia., bears N.45°W., 150 lks. dist.

Doug. County Surveyors Office - James W. Byron, Deputy - For:
Douglas Co. Road Dept. Milo Godfrey & C. Putnam, Crew
Oct. 24, 1960 - C.S. File 52/58

Found - Orig. 20" now 42" Fir (N.48°E. record) we find
should be N.55°E., 38.3 ft., shows old bark
scribing.
Orig. 60" now 60" Fir (N.45°W. Record). We find
should be N.25°W., 99.0 ft., shows old bark
scribing.
Orig. 20" now 42" Fir S.88°W., 43.6 ft. shows good
scar. I do not open.
Also find old scribed stake on ground at corner.
Set Brass cap at cor. mkd: County Surveyors S 2 | S 1 T26SR3W
Office, 1960 S 11 | S 12
New BTs - 8" W.Fir bears N.54°W., 16.0 ft. scribed S2 T26S R3W
CS BT.
14" R.Fir bears S.50°W., 19.0 ft. scribed S11 T26S
R3W CS BT.
7" R.Fir bears N.62°E., 25.3 ft. scribed S1 T26S R3W
CS BT.
19" R.Fir bears S.79°E., 16.9 ft. scribed S12 T26S
R3W CS BT.

Found OK, BLM resurvey, White; Beck & Reynolds, 1962,1963
(DCSO records, Vol. 32 Page 13376)

Found OK, Jan. 10, 1978, Gary Langlitz, C.S. File 59/46-17
Doug. County Surveyors Office

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause -
2/27/2008 - C.S. File 67/25-28

Found Ok, 4 live BTs orig. 60" Fir now 40' tall snag 14" Fir,
S.50°W., 19.0 ft. now gone.

continued next page

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor Secs. 1, 2, 11, & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2822, surveyed Feb./March 2016- (DCS0 records Vol. 59 Page 23630-1)

The cor. of secs. 1, 2, 11, and 12, monumented with an iron post, 1¼" dia., loosely set, projecting 26 ins. above ground, with a brass cap (properly) mkd. from which the remains of the original BTs reported by White et. al., in 1962-63

A roothole, bears S.86¾°W., 43.6 ft., alongside of which is a down fir, 42" dia., with a healed blaze.

A fir snag, 60" dia., bears N.24¼°W., 99.0 ft., with no marks visible.

and the remains of the BTs mkd. by Byron, in 1960 and reported by White et. al.

A fir snag, 9" dia., bears N.62¾°E., 25.7 ft., with a healed blaze.

A roothole bears S.78½°E., 17.8 ft., alongside of which is a down fir, 19" dia., with a healed blaze.

A fir, 12" dia., bears N.54¾°W., 16.2 ft., with a healed blaze.

At the corner point

Reset the iron post, 32" long, 28" in the ground and deposit a magnet in a white plastic case at the base of the cor.

from which new accessories

A fir, 20" dia., bears N.80¼°E., 36.0 ft., mkd. T26S R3W S1 BT.

An iron rod, 30" long, 5/8" dia., driven 26" in the ground for a reference monument, bears S.41°42'29"E., 5.0 ft., with an aluminum cap mkd. RM T26S R3W S12 5.0 FT TO COR and an arrow pointing to the cor.

An iron rod, 30" long, 5/8" dia., driven 28" in the ground for a reference monument, bears S.41°13'05"W., 5.0 ft., with an aluminum cap mkd. RM T26S R3W S11 5.0 FT TO COR and an arrow pointing to the cor.

Corner is located on a NW. slope.

NAD 1983 (2011)

Latitude: 43°19'47.03" N. Longitude: 123°00'39.56" W.