

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Samuel C. Flint, Under Group #454, dated June 19, 1882 (DCSO Records, Vol. 11 Page 4398)

Set Cedar post, 3 ft. long, 3" sq., firmly in the ground for 1/4 sec. cor. marked 1/4 S on E and W faces, around which I put a pile of stones, no trees being near.

Arthur Boyer, Deputy Co. Surveyor - Wit: B.A. Lane Maurice Reid; Wldon Stone; Pickett McMillan - May 20, 1937 C.S. File 30/21A and "Old" Cor. Book, Page 190

Set from evidence on ground - E and W fence and pile of rocks confirmed on the ground by Pickett McMillan who saw original stake as set by US GLO for this 1/4 cor. and also by F.C. Frear who also saw this original stake as witnessed by McMillan.

Set 10 gauge shot gun barrel in ground and scribed:

A Fir 15" dia., N.27 1/2°E., 28 ft.
A Fir 18" dia., S.83°E., 14.7 ft.

Doug. County Surveyors Office - James Byron - For: Douglas County Road Dept. Wit: Milo Godfrey and C. Putnam Oct. 1960 - C.S. File 52/58

Found shotgun barrel at corner & both BTs, now stumps, show good scars, check bearing & distances.

New BTs - 7" R.Fir bears S.73°W., 3.6 ft. scribed 1/4 S2 CSBT
18" R.Fir bears S.39 1/2°E., 20 ft. scribed 1/4 S1 CSBT

Bureau of Land Management resurvey by White, Beck and Reynolds Under Group #'s 242, 491, 527 - Survey, June 1962-Aug. 1963 (DCSO records, Vol. 32 Page 13377)

The 1/4 cor. perpetuated and recorded by A. Boyer, in 1937, monumented with a shotgun barrel in a mound of stone, and rehabilitated by J. Byron in 1960, from which the remains of the bearing trees marked by Boyer:

A Fir stump 26" dia., bears N.26 1/2°E., 43 lks. dist. with a healed blaze.

A Fir stump 24" dia., bears S.83 1/2°E., 23 1/2 lks. dist., with a healed blaze.

(Cont. Next Page)

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Monument in Fir and Cedar woods.
NW quadrant cleared on moderate South slope.
Compass decl. 14½°E.
Lat: 43°20'14.34"N Long: 123°00'39.16"W