

PRIMARY CORNER DESCRIPTION Sec. Cor. 1 & 2; 35 & 36 of T.25-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855 (DCSO Records, Volume 9 Page 3664)

Set post cor. to secs. 1, 2, 35 and 36, from which

- A Cedar 12" dia., bears N.1°E., 22 lks. dist.
- A Red Fir 20" dia., bears N.39°W., 25 lks. dist.
- A Red Fir 28" dia., bears S.82°W., 33 lks. dist.
- A Maple 2" dia., bears S.62°E., 18 lks. dist.

GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April 5, 1940 (DCSO records, Volume 27 Page 11507)

Proportional measurement. Set an iron post, 3 ft. long 2" dia., 28" in the ground, for cor. of secs. 1, 2, 35 & 36, with brass cap marked:

T25S R3W
<u>S35 S36</u>
S2 S1
T26S
1943

from which

- A Fir 20" dia., bears N.30°E., 8 lks. dist., mkd. T25S R3W S36 Bt.
- A Fir 24" dia., bears S.72°E., 81. lks. dist. mkd. T26S R3W S1 BT.
- A Fir 20" dia., bears S.84°W., 50 lks. dist. mkd. T26S R3W S2 BT.
- A Fir 20" dia., bears N.57½°W., 40 lks. dist. mkd. T25S R3W S35 BT.

Fd. OK by H.Christensen, Apr. 1998 - M 128-59
 Fd. OK by H.Christensen, Oct. 1999 - M133-77

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 11/8/2007 - C.S. File 67/24-43

Found - 2½" dia., brass cap properly marked on 2" O.D. Iron pipe, projects 14" above ground in mound of stones.

- 20" now 31" dia., x 1½ ft. tall D.Fir stump, tagged. No marks visible bears N.30°E., 6.0 ft. (Rec. N.30°E., 5.3 ft.) 1943 BT.
- 24" now 40" dia., x 2½ ft. tall D.Fir stump, tagged, healed rotted blaze bears S.72°E., 53.5 ft. (agrees w/rec) 1943 BT
- 20" now 29" dia., x 4 ft. tall D.Fir stump, tagged, burline visible on rotting stump bears S.84°W., 33.0 ft. (agrees w/rec) 1943 BT. cont.....

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Sec. Cor. 1 & 2; 35 & 36 of T.25-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New -	20" now 34" dia., D.Fir, healed blaze, bears N.57½°W., 26.4 ft. (agrees w/rec) 1943 BT
	8" dia., hemlock double blazed & scribed "T26S R3W S1 CS BT" bears S.13°E., 40.7 ft.
	6" dia., Chinquapin double blazed & scribed "T26S R3W S2 CS BT" bears S.24½°W., 18.0 ft.
Note -	Corner lays on nearly flat E-W bench. Compass decl. 16¼°E.