

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 620540

PRIMARY CORNER DESCRIPTION West Center 1/16, Sec. 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Doug. County Surveyors Office - Gary Langlitz; L.E. Monrean  
S.J. Flause; Frank Silagy - March, 1978 - C.S. file 60/7  
M 65-73

-----  
Corner location determined by survey.

Set - At the corner point WE SET a 1" x 30" I.P. 27" in  
the ground with brass cap attached marked:  
Douglas Co. Surveyor T 26 S  
1978 C W 1/16 C  
S 12  
R3W

BTs - 16" Red Cedar scribed "CW 1/16 S12 CS BT" on a  
double blaze, bears N.1°W., 37.3 ft.  
24" D.Fir scribed "CWS 1/16 S12 CS BT" on a  
double blaze bears S.83°E., 101.9 ft.

Corner located along E-W cutting line approx. 200 ft. west of  
small creek.

FD. Ok, Red Cedar OK, D.Fir now 30 ft. tall snapped off but  
still alive - DCS0 2/26/2008, J. Pike & S. Flause, C.S. File  
67/25-20

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff  
Lorsung- 1/24/2023 - C.S. File 67/55-28

-----  
Found - DCS0 brass cap (properly mkd) proj. 8"  
Burned out shell, 18"x8' R.Cedar, N.1°W., 37.3 ft.  
28"x30 ft burned snag S.83°E., 101.9 ft., healed  
upper blaze, lower blaze burned out.

New - 12"x2½' sawn burnt maple stump S.72°E., 22.0 ft.,  
3½" mag nail top center.  
11"x13 ft. burned broken top Fir snag S.5½°W., 21.5  
ft. 3½" mag nail right side center.  
12"x1½ ft burned sawn fir stump S.42°W., 13.0 ft.,  
3½" mag nail right side center.

Note - Area burnt 9/2020  
Compass decl. 14½°E.

Lat: 43°19'20.59" N Long: 123°00'21.11"W