

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Samuel C. Flint, Under Contract #454 dated June 19, 1882 (DCSO records, Vol. 10 Pages 4385)

Set Cedar post, 3 ft. long, 3" sq., firmly in the ground for 1/4 sec. cor. mkd. on N face 1/4 S - - - and on the S face 1/4 S, from which
A Fir 20" dia., bears S.20°E., 35 lks. dist. mkd. 1/4S BT.
A Fir 20" dia., bears N.65°W., 18 lks. dist. mkd. 1/4S BT.

Bureau of Land Management resurvey by Wayne L. Rogers, Under Contract #1058 Survey June/Aug. 1981 (DCSO records Vol. 45 Page 17437)

Point for the 1/4 sec. cor. at proportionate distance; there is no remaining evidence of the orig. corner.
Set an iron post, 28" long, 2 1/2" dia., 26" in the ground with a brass cap mkd.
T 26 S R 3 W
1/4 S 25
S 36
1981

from which
A Fir 14" dia., bears S.22 1/2°E., 40 1/2 lks., mkd. 1/4 S36 BT.
A Fir 37" dia., bears N.51°W., 17 1/2 lks., mkd. 1/4 S25 BT.

Doug. County Surveyors Office - Randall Smith & Stephen Flause January 19, 1990 - C.S. File 64/5-5

Found - 1981 3 1/4" BLM brass cap on a 2 1/2" O.D. Iron pipe, protruding 3" above ground.
37" now 37" dia. down & out of position D.Fir with an unhealed single blaze scribing visible "1/4 S26 BT", root hole bears N.51°W., 11.6 ft.
14" now 14" dia. D.Fir with a fully healed single blaze bears S.20°E., 26.7 ft. (Rec. S.22 1/2°E., 26.7 ft.)
New BTs - 13" dia. D.Fir double blazed & scribed "1/4 S36 CSBT bears S.84°W., 9.8 ft.
6" dia. I.Cedar double blazed & scribed 1/4 S25 CSBT bears N.45°W., 37.8 ft.
6" dia. I.Cedar double blazed & scribed 1/4 S25 CSBT bears N.48 1/2°E., 37.1 ft.
Cor. lies in a E-W cut line approx. 300 ft. NE of end of road

continued next page

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Dependent resurvey by Jeffrey O Covington, cadastral Surveyor under Group 2953, Surveyed Sept/Oct 2019 (DCSO Records Vol. 59 Pages 23986-23988 and Plat maps T26-3 2021-1 thru 2021-3)

The ¼ sec. cor. of secs 25 and 36, reported by Rogers in 1981; and perpetuated by Monrean, in 1990; monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with a brass cap (properly) mkd.

from which the remains of a BT reported by Rogers

A roothole bears N.51°W., 11.6 ft., alongside of which is a down fir trunk, 37" dia., with scribe marks ¼ S25 BT visible on partially healed blaze.

and the remains of the BTs mkd. by Monrean

A cedar, 20" dia., bears N.48¾°E , 36.6 ft., with a healed blaze.

A fir, 18" dia bears S.79¾°W., 10.4 ft., with a healed blaze.

A cedar snag, 7" dia., bears N.46°W., 37 7 ft., with scribe marks BT visible on partially healed blaze.