

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 640620

PRIMARY CORNER DESCRIPTION CS 1/16 SEC 1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM resurvey by White, Beck and Reynolds, Group #'s 242, 491, 527 - Survey June, 1962-Aug. 1963 - (DCSO records, Vol. 32 Page 13393

Point for the center S 1/16 sec. cor. of sec. 1. Set and iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap marked

C
S 1/16 | S 1
C
1963

from which

A fir, 23" dia., bears N.24°E. 31 lks. dist., mkd. CS 1/16 S1 BT.

A fir, 22" dia., bears N.84°W. 34 lks. dist., mkd. CS 1/16 S1 BT.

From this point a bolt, ¾" dia., firmly set, protruding 1" above the ground, bears S.88°50'W., 0.148 chs. dist. at a point determined by the County Surveyor, in 1947.

Found ok by Bruce Shaner - 10/1965 - M30-48
Found ok by Andrew Ausland - 2/2012 - St. Hwy. 138-013 B

Douglas Co. Surveyor's Office - Crew: Stephen J. Flauser and Jeff Lorsung - 2/17/2026 - C.S. File 67/62-14

Found - 3¼" BLM brass cap proj. 7".
Burnt - sawn 26" x 2½ ft. D. fir stump N.24°E. 19.7 ft. (Rec 31 lks 20.5 ft slope) Add 3½" mag nail top center. Fully healed single blaze.
Burnt - sawn 26" x 3 ft. N.84°W. 22.4 ft. fully healed single blaze. Add 3½" mag nail top center.
Bolt 1⅛" square head and 3" round collar 2" below top. S.88°50'W. 9.1 ft. (Rec. 0.148 chns)
Alum. post 0.5 ft. westerly.

Notes - Area burnt 9/2020
Mon. is on small bench on a moderate west slope in plot cleared after 2020. Fire approx. 55 ft. west of abandoned forest road.

Compass decl. 14¼°E.
TRIMBLE GEO XT POSITION
43°.33298760 N. 123°.00098746 W.