TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 640660

PRIMARY CORNER DESCRIPTION CN 1/16 Sec 1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Arthur Evans - Aug 1954 - M11-15 & C.S. File 41/298

Set 4"x4"x36" Cedar stake by prop. meas.
BL & SCR 2 BTs
9" W.F. N.32°W., 40.6 ft.
8" W.F. S.28°E., 18.9 ft.

Bureau of Land Management Subdivision of Section by C. White; D. Beck & P. Reynolds - Under Group #'s 242, 491 and 527 Survey, June 1962-Aug. 1963 (DCSO records, Vol. 32 Pg13394-5)

Point for the center N 1/16 sec. cor. of sec. 1.
Set an iron post, 28" long, 2½" dia., 21" in the ground, with brass cap marked

C
N 1/16 S 1
C
1963

from which
A fir, 15" dia. bears S.82¾°E., 48 lks., mkd CN 1/16 Sl BT
A fir, 14" dia. bears N.49½°W., 149 lks. mkd CN 1/16 Sl BT

From this point a wood stake, 2" square, firmly set, protruding 30" above the ground, bears S.46°30'W., 0.08 chs., at a point determined by A. R. Evans, in 1954., from which
A fir snag, 10" dia., bears S.27°E., 28 lks. mkd. CN 1/16 S1 BT on opened blaze.
A fir stump, 10" dia., bears N.31½°W., 62 lks., and the fallen tree bears scribe marks CN 1/16 S1 BT.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 2/18/2026 - C.S. File 67/62-16

Found - 3¼" BLM brass cap, proj 4".
Burned and sawn 30"x 1/2 ft. Hemlock stump S.82¾°E., 31.7 ft. No blaze evident.
New - Burned-sawn 18"x1½" D.Fir stump S.33½°W., 12.6 ft. 3½" mag nail top center.
Note - Area burnt 9/2020
Compass decl. 14¼°E.
Mon on large bench approx. 60 ft. NE of gravel parking area.
Trimble GEO XT position
43.34013943°N
123.00082319°W.,