

PRIMARY CORNER DESCRIPTION Tps Cor. T26-2 & T26-3 (South)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Addison R. Flint, Contract #56 dated March, 1855 (DCSO Records, Volume 10 Page 4353)

-----  
Set post, cor. to secs. 1, 6, 31 and 36, from which  
A Laurel, 7" dia., bears S.47°W., 64 lks. dist.  
A Red Fir 6" dia., bears S.85°E., 18 lks. dist.  
A Laurel, 6" dia., bears N.83°W., 50 lks. dist.  
No trees convenient NE.

Charles M. Collier, under Special Instructions dated May 12, 1913 (DCSO records, Volume 10 Page 4257)

-----  
Intersect the point for cor. of Tps. 26 and 27 S., Rs. 2 and 3 W., located by reference to the SE bearing tree: all other traces of the cor. have disappeared. I now re-establish this cor. in its original position, as follows:  
Set a fir post, 3 ft. long, 4" sq. 24" in the ground, for cor., marked T26S S31 on NE., R2W S6 on SE., T27S S1 on SW and R3W S36 on NW faces, with 6 notches on each edge:  
from which  
A Laurel 5" dia., bears N.12°30'E., 76 lks. mkd. T26S R2W S31 BT.  
A Fir 30" dia., bears S.85°E., 18 lks. mkd. T27S R2W S6 BT (Original BT)  
A Fir 30" dia., bears S.16°W., 15 lks., mkd. T27S R3W S1 BT.  
A Laurel, 5" dia., bears N.11°30'W., 77 lks., mkd. T26S R3W S36 BT.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2331, Surveyed April/Oct. 2011 - (DCSO records Vol. 58 Page(s) 22919)

-----  
MEMORANDUM (Pg 22197):  
The cor. of Tps. 26 and 27 S., Rgs. 2 and 3 W., was established by A. Flint in 1855 while surveying the S. bdy. of Tp. 26 S., R. 3 W. A position was also established by S. Flint in 1882, while surveying the E. bdy. of Tp. 27 S., R. 3 W. and given the same cor. designation. The cor. positions were erroneously reported as common in the resurveys performed by Collier and Corbin, but now function as the cors. of their respective townships.

-----  
The cor. of Tp. 26 S., Rgs. 2 and 3 W., established by A. Flint in 1855, formerly designated as the cor. of Tps. 26 and 27 S., Rgs. 2 and 3 W., perpetuated by Collier in 1913-14, at record bearing and distance from the remains of the original SE. bearing tree  
continued next page

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION Tps Cor. T26-2 & T26-3 (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A sawed fir stump, 46" dia., bears S.85°E., 11.9 ft., with scribe marks BT visible on a partially opened blaze. from which the remains of a bearing tree mkd. by Collier

A sawed fir stump, 58" dia., bears S.16°W., 9.9 ft., with scribe marks R3W visible on a partially opened blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 27" in the ground, with brass cap mkd.

T 26 S  
R3W R2W  
S 36 | S 31  
S 1  
T27S R3W  
2011

from which new bearing trees

A fir, 6" dia., bears N.40¼°E., 20.0 ft., mkd. T26S R2W S31 BT.

A fir, 16" dia., bears N.54°W., 9.9 ft., mkd. T26S R3W S36 BT.

This cor. is now designated as the cor. of Tp. 26 S., Rgs. 2 and 3 W.

(The Tps corner for T27-2 & T27-3 (north) bears N.68°09'06"E. 41.24 ft)