

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Sec. Cor. 13 & 24; 18 & 19 of T26-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855  
(DCSO Records, Volume 10 Page 4178)

-----  
Set post cor. to secs. 18, 19, 13 and 24, from which  
A Laurel 15" dia., bears S.5°W., 190 lks. dist.  
A Laurel 12" dia., bears S.17°E., 140 lks. dist.  
A R. Fir 5" dia., bears N.88°W., 10 lks. dist.  
A R. Fir 12" dia., bears N.85°E., 20 lks. dist.

GL0 survey by William N. Gibb, Under Contract #783 dated  
December 1908 (DCSO records, Volume 10 Page 4248-9)

-----  
Cor. secs. 13, 18, 19 and 24, which is a stake greatly  
decayed, marked as described by the Surveyor General. Bearing  
trees have been destroyed.

Set granite stone, 7x11x15 ins., 10" in the ground, marked  
with 4 notches on N and S edges, from which  
A Fir 24" dia., bears N.53°E., 108 lks. dist., marked  
T26S R2W S18 BT.  
A Fir 24" dia., bears S.80°E., 31 lks. dist., marked  
T26S R2W S19 BT.  
A Laurel 12" dia., bears S.5°W., 190 lks. dist., marked  
T26S R3W S24 BT.  
A Fir 17" dia., bears N.15°W., 12 lks. dist., marked  
T26S R3W S13 BT.

Doug. County Surveyors Office - Vernon Tracy; M. Darby; T.  
Connell - June 1965 - C.S. File 54/7-32

-----  
Found - Stone 4x12x15", firmly set, shows notches on S & N.  
17" Fir N.15°W., 7.3 ft. now stub 5.0 ft. high,  
rotted & burned, shows scribe.  
24" now 24" snag Fir (?) S.84°E., 26.6 ft. record  
S.80°E., 20.5 ft., shows old axe marks in ark,  
no scribe found.  
24" now 28" Fir, alive, N.53°E., 78.8 ft. record  
71.3 ft. open & shows scribe.

Set brass cap at cor mkd. County Surveyors T26S S13|S18  
Office, 1965 R3W S24|S19 R2W  
New BTs - 6" D.Fir S.87°W., 13.1 ft. mkd. T26S R3W S24 CS BT.  
6" D.Fir N.74°W., 25.4 ft. mkd. T26S R4W S13 CS BT.  
No tree large enough to SE - Orig. NE BT OK.  
See BTs, Weyerhaeuser Nails & Plates in C.S. 53/115-16;55/19

continued next page

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Sec Cor. 13 & 24; 18 & 19 of T26-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Harley Case under the supervision of John Wilson, Washington Licensed Eg Reg #2526, Weyco - Glen McChesney, Weyco - BLM crew: Hal Brusche, T Watts & M Berg - Aug. 1965 - C.S. 55/19-1

-----  
Found the above mentioned BTs as noted by DCSO in Aug. 1965 and Referenced by Glenn McChesney (Plates and "W" nails only)  
Declination 20°  
28" Fir N.54°E., 77.6  
6" Hemlock N.24°E., 13.0'  
6" Fir S.86°W., 13.1'  
9" Fir S.25°W., 19.0'

Nick Juliano, Weyco - Oct. 1978 - C.S. File 58/184-1

-----  
Found - DCSO Brass cap  
10" hemlock, N.24°E., 13.0', W. CO. Tag & nail.  
12" fir, S.25°W., 19.0', W. CO. Tag & nail.  
8" fir, S.86°W., 13.1' scribed, W. CO. Tag & nail.  
8" fir, N.74°W., 22.4', scribed, BLM tag.

BLM dependent resurvey by Joel R Herzberg, Cadastral Surveyor under Group No. 2817, surveyed Oct./Nov. 2015 - (DCSO records Vol. 58 Page(s) 23487 & Plat T26-2 2017-1)

-----  
The cor. of secs. 13, 18, 19, & 24, on the W. bdy. of the Tp. perpetuated by the Douglas Co. Surveyor's Office in 1965, from original evidence no longer in existence, monumented with an iron pipe, 1¼" dia., firmly set, in a rock outcrop, projecting 6" above the ground, with brass cap (properly) mkd from which new accessories

A fir, 16" dia., bears N.46½°E., 113.3 ft., mkd. T26S R2W S18 BT.

A rock cut bank, 15 ft. high, bears S.8°58'37"W., 36.30 ft., to a Mag-Nail driven in crack, with marks B0 chiseled in the rock face, 3 ft. high up the rock face.

A fir, 9" dia. bears N.32°W., 54.3 ft. mkd T26S R3W S13 BT  
Corner is located S., 35 ft., from a gravel road, 12 ft. wide, extending N.80°E. and S.80°W.

From this cor., a point established as a witness cor. for the cor. of secs. 13, 18, 19, & 24, on the W. bdy. of the Tp., by Glenn S. Baughman, in 1980, in an unfiled survey, bears S.0°07'32"E., 57.57 ft., and is accepted as a reference monument, monumented with an iron pipe, 2" dia., firmly set, projecting 2" above the ground in a collar of stone, with brass cap mkd. WC T26S R3W S13 S18 R2W S24 S19 1980 LS 536.

continued next page

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Sec. Cor. 13 & 24; 18 & 19 of T26-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Dependent resurvey by Jeffrey O Covington, cadastral Surveyor under Group 2953, Surveyed Sept/Oct 2019 (DCSO Records Vol. 59 Pages 23986-23988 and Plat maps T26-3 2021-1 thru 2021-3)

-----  
The cor. of secs. 13, 18, 19, & 24, on the E bdy. of the Tp., reported by Herzberg in 2015, monumented with an iron post, 1¼" dia., firmly set, in a rock outcrop, projecting 6" above ground, with a brass cap(property) mkd.

from which the accessories reported by Herzberg

A fir, 16" dia., bears N.46½°E., 113.3 ft., with a healed blaze.

An iron post, 2" dia., firmly set, projecting 2" above ground, in a collar of stone, bears S.0°07'32"E., 57.57 ft., with a brass cap mkd . WC T26S R3W S13 S18 R2W S24 S19 1980 LS 536.

A rock cut bank, 15 ft. high, bears S.8°58'37"W., 36.30 ft., to a Mag-Nail driven in crack, with marks B0 chiseled in the rock face, 3 ft. high up the rock face.

A fir, 11" dia. bears N.32°W., 54.3 ft., with a healed blaze.

From the corner, N.89°26'39"W.;

145 ft. dist., graveled road, 10 ft. wide, bears N.55°E. and S.45°W.

1280 ft. dist., creek, 5 ft. wide, course N.20°E.

2405 ft. dist., graveled road, 18 ft. wide, bears N.20°E and S.50°W.