

PRIMARY CORNER DESCRIPTION 1/4 Cor. for 12 & 7 of T.26-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Contract #56 dated March, 1855  
(DCSO Records, Volume 10 Page 4179)

-----  
Set 1/4 sec. post, from which  
    A R.Fir 12" dia., bears S.15°W., 20 lks. dist.  
    A Maple 3" dia., bears S.12°E., 8 lks. dist.

-----  
GLO survey by Charles Collier Under Instructions dated May 12,  
1913 (DCSO records, Volume 10 Page 4252)

-----  
Intersect the point for the 1/4 sec. cor., located by reference  
to the SW. bearing tree as described by the surveyor general;  
all other traces of the cor. have disappeared. I now re-  
establish this cor. in its original position as follows:  
Set a basalt stone, 14x8x6 Ins., 9" in the ground for cor.  
mkd. 1/4 on W face; from which  
    A Fir 20" dia., bears S.15°W., 20 lks. dist., marked  
    1/4 S B T. (Orig. BT)

-----  
BLM resurvey by Zirpel & Glenn - May/Oct. 1959 Under  
Instructions dated Nov. 1958, Group #404 - (DCSO Volume 30  
Page 12723)

-----  
Found the 1/4 cor. of secs. 7 & 12, marked by a mound of stone,  
3 ft. base, 1 1/2 ft. high, from which the only remaining  
original bearing tree:

    A down an rotted fir stump, 22" dia., bears S.15°W., 20  
    lks. dist., no scribe marks visible, but cruiser  
    mark X on bark.

and locally established bearing trees

    A fir 50" dia., bears N.45°E., 49 lks. dist., mkd.  
    with a Weyerhaeuser metal bearing tree tag.

    A fir 20" dia., bears S.63°W., 54 lks. dist., mkd.  
    with a Weyerhaeuser metal bearing tree tag.

At the corner point, at center of mound of stone

Set an iron post, 28" long, 2 1/2" dia., 10" in the ground, and  
in a mound of stone, 3 ft. base, to top, with brass cap mkd.

    T 26 S  
    R 3 W R 2 W  
    1/4  
    S 12 | S 7  
    1959

from which new bearing trees

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 12; & 7 of T.26-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A Cedar 15" dia., bears N.81½°E., 70½ lks. dist., mkd.  
¼ S7 BT.  
A Cedar 12" dia., bears N.62°W., 30 lks. dist., mkd.  
¼ S12 BT.

Doug. County Surveyors Office - R.B. Kimberling; F.C. Silagy  
Dec. 30, 1977 - C.S. File 59/42-36

-----  
Found - 1959 Cadastral Brass cap, set in a 1.0 ft. high 3.0  
ft. mound of stone, 13" above ground.  
20" Fir(down) bears S.63°W., 35.6 ft. with a well  
healed blaze. (nor record of marking tree.)  
15" Cedar, dead, bears N.81½°E., 46.5 ft. with  
visible scribing "¼ S7 BT" in partially healed  
single blaze.  
12" now 14" Cedar bears N.62°W., 19.8 ft. with  
visible scribe marks in almost healed blaze.  
New BT - 50" D.Fir bears N.45°E., 32.3 ft. single blazed and  
marked "1/4 S7 CS BT".  
Corner is 150 ft. south of south bank, North Umpqua River.