

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12; 6 & 7 of T26-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 10 Page 4179)

Set post cor. to secs. 1, 12, 6 and 7, from which
A Cedar 8" dia., bears S.60°E., 15 lks. dist.
A Cedar 15" dia., bears S.60°W., 30 lks. dist.
A Cedar 13" dia., bears N.68°E., 30 lks. dist.
A R.Fir 16" dia., bears N.46°W., 88 lks. dist.

GLO survey by W.H. Byars, Contract #317, Jan. 20, 1879
(DCSO records, Vol. 10 Page 4381)

Said post was found rotted down., witness trees all standing:
A Cedar 20" dia., bears N.68°E., 30 lks. dist.
A Cedar 16" dia., bears S.60°E., 15 lks. dist.
A Cedar 24" dia., bears S.60°W., 30 lks. dist.
A Red Fir 20" dia., bears N.46°W., 88 lks. dist.
Trees same as notes furnished except their growth.
Set new cedar post, 36" long, 10" wide, 4" thick, 20" in
ground.

GLO resurvey by Charles M. Collier, Under Instructions dated
May 12, 1913 (DCSO records, Volume 10 Page 4253)

Point for corner located by reference to the bearing trees as
described by the surveyor general; all traces of corner have
disappeared. I re-establish this cor. in its original position
as follows:
Set a basalt stone, 14x7x7 ins., 9" in the ground, marked with
5 notches on S. and 1 notch on N. edge; witnessed by the orig.
bearing trees as follows:
A Cedar 13" dia., bears N.68°00'E., 30 lks. dist.,
marked T26S R2W S6 BT.
A Cedar 8" dia., bears S.60°E., 15 lks. dist., marked
T26S R2W S7 BT.
A Cedar 15" dia., bears S.60°W., 30 lks. dist., marked
T26S R3W S12 BT.
A Red Fir 16" dia., bears N.46°W., 88 lks. dist., marked
T26S R3W S1 BT.

BLM resurvey by Zirpel & Glenn, May/Oct. 1959 under Special
Instructions dated Nov. 1958, Group #404 (DCSO records,
Volume 30 Page 12724)

(Cont. Next Page)

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12; 6 & 7 of T.26-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Found the cor. perpetuated with an iron pipe 2" dia., protruding 36" above ground, firmly set, at record bearing and distance from each or the two remaining original bearing trees:

A Cedar 36" dia., bears S.60°W., 30 lks. dist., with a healed blaze.

A Fir 30" dia., bears N.46°W., 88 lks. dist., with scribe marks T26S R3W S1 visible on a partially opened blaze.

and locally established bearing trees

A Hemlock 10" dia., bears N.37°E., 17½ lks. dist., mkd. with a partially healed blaze and a nail stamped W on head. Re-mark this tree T26S R2W S6 BT.

A Cedar 12" dia., bears S.73°E., 41 lks. dist., mkd. with a nail stamped W on head. Re-mark this tree T26S R2W S7 BT.

At corner point, set an iron post, 28" long, 2½" dia., 24 ins. in the ground, with brass cap mkd:

T	26	S
R	3	W
R	2	W
S	1	S
S	12	S
		6
		7
		1959

Deposit the iron pipe alongside the iron post.

BLM resurvey by White; Beck and Reynolds, June 1962 to Aug. 1963 Under special instructions dated Aug. 1963 under Group No. 491; 242;527. (DCSO records, Volume 32 13372)

Found 1959 brass cap protruding 7" above ground, from which the remaining original bearing trees

A Fir stump 30" dia., bears N.46°W., 88 lks. dist., with scribe marks T26S R3W S1 visible on partially opened blaze.

and 1959 bearing tree

A Hemlock 10" dia., bears N.37°E., 17½ lks. dist., mkd. T26S R2W S6 BT.

A Cedar 12" dia., bears S.73°E., 41 lks. dist., mkd. T26S R2W S7 BT.

add one new bearing tree

A Fir 35" dia., bears S.66°W., 123 lks. dist., marked T26S R3W S12 BT.

(Cont. Next Page)

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Sec. Cor. 1 & 12; 6 & 7 of T.26-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Doug. County Surveyors Office - R.B.Kimberling; P.L.Earle;
S.J. Flause - Jan. 10, 1978 - C.S. File 59/46-14

Found - 1959 Cadastral brass cap on a 2½" I.P. 7" above
ground properly marked.
15" now 36" Cedar stump is pushed over. Orig.
position bears approx. S.60°W., 19.8 ft. but no
visible blaze. (OBT)
Remains of a Fir stump bears N.46°W., 58.1 ft. (OBT)
12" now 13" Cedar snag bears S.73°E., 27.1 ft. with
scribing "T26S R2W S7 BT" in single blaze.
(1959 resurvey)
50" Fir stump with a Weyerhaeuser tag and blaze
bears S.60°W., 35.0 ft.
28" Fir stump with a Weyerhaeuser tag and blaze
bears N.59°W., 47.4 ft.
New BTs - 13" Cedar with "MR" carved in West face bears
N.83°E., 20.0 ft. double blazed and scribed
"T26S R2W S6 CS BT"
10" D.Fir bears S.20½°E., 124.1 ft. double blazed
& scribed "T26S R2W S7 CS BT".
3" "X" chiseled 3 ft. above ground in a 20 ft. x 20
ft. boulder bears S.88½°W., 32.0 ft.
6" Chinquapin bears N.50°W., 71.8 ft. double blazed
and scribed "T26S R3W S1 CS BT".
Corner is 30 ft. north of road.

See C.S. File 53/114-3 for Weyerhaeuser 1969 corner report.
Added two new references, described in above DCSO corner
visit.

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike
- 11/8/2007 - C.S. File 67/24-46

Fd. Ok, as per 1978 renewal.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral
Surveyor, under Group No. 2923, surveyed July 2018/March 2020-
(DCSO records Vol. 59 Pages 24046-7)

The cor. of secs. 1, 6, 7, & 12, reported by White, Beck, and
Reynolds in 1962-63; perpetuated by the Douglas County
Surveyor's Office in 1978; monumented with an iron post, 2½"
dia., firmly set, projecting 8" above ground, (alongside of
which is an iron pipe, 2" dia., firmly set, projecting 30"
above ground) with a brass cap (properly) mkd. Cont.

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Sec. Cor. 1 & 12; 6 & 7 of T.26-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of a bearing tree mkd. by person(s) unknown, reported by the Douglas County Surveyor's Office
A decayed fir stump, 24" dia., bears N.61¼°W., 47.4 ft., no marks visible.
and the accessories established by the Douglas County Surveyor's Office
A cedar, 27" dia., bears N.81¼°E., 19.6 ft., with a healed blaze.
A fir, 20" dia., bears S.23¾°E., 127.0 ft., with a healed blaze.
A boulder, 20x20x4 ft. high, bears S.86½°W., 32.1 ft., with a chiseled X on the E. face.
A tan oak, 9" dia., bears N.52¼°W., 71.8 ft., with a healed double blaze.
Corner is located N., 65 ft., of a graveled road, 20 ft. wide, bears S.55°E. and N.60°W.
NAD 1983 (2011)
Latitude: 43°19'44.75" N. Longitude: 122°59'28.27"W.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 9/16/2022 - C.S. File 67/54-18

Found - 3¼" BLM brass cap on 2½" I.Pipe, up 8" - 2" I.Pipe on WNW edge of brass cap, up 30"
Burnt-dead 28" Cedar N.83°E., 20.0 ft., burnt out face. 1978
A 3"x3' above ground in 20x20' boulder S.86°W., (rec. S.88½°W.) 32.0 ft.
8"x7' sawn chinquapin stump N.53°W., (rec. N.50°W.) 71.8 ft., healed double blaze.
New - 5/8"x30" I.Rod with DCS0 yellow plastic cap, S.5°W., 63.4 ft in fill slope of road shoulder, projecting 3".
Note - Corner is 30±" of road.
Compass decl. 14½°E.
See sketch in file.
OCRS state plane co-ordinates
Cottage Grove - Canyonville Zone (SEE 2018/2020 BLM Report for Lat/long)
N 180887.011 E 255081.218