

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 700640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 1; & S. 6 of T. 26-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Doug. County Surveyors Office - V. Tracy and crew - Aug. 11, 1967 - C.S. File 54/40-56

Found - 1963 Cadastral brass cap set in mound of stone.
Orig. 40" Fir now sawed stump, S.88°E., 14.5 ft. shows bark scribe.
50" Fir N.2°W., 31.0 ft., alive, shows bark scribe in poor condition.
18" Cedar S.53½°E., 27.1 ft. (1963 BT)
New BT - 9" Hemlock N.53°W., 29.3 ft. mkd. ¼ S1 CS BT.
This corner lies on top of ridge course NE and SW. at NE corner of cut-off unit.

Kevin Schinnell - For: Rosboro Lumber Co. - 1/2006 - M 149-35

Found - 3¼" brass monument on 3" iron pipe & accessories as follows:
24" cedar S.55°E., 26.22'
14" hemlock N.48°W., 29.72'
56" fir N.02°E., 28.44'
New - 20" hemlock S.82°W., 7.35'
Note - All accessories repainted and flagged at this time.

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 11/28/2007 - C.S. File 67/24-47

Found ok as noted:
24" cedar - ok
14" hemlock - ok
56" Fir, now low stump
20" hemlock S.82°W., 7.35' is not scribed, there is a low notch with nail & dist. 7.35 ft. is measured from nail to BC (face meas.)

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24048)

The ¼ sec. cor. of secs. 1 and 6, reported by White, Beck, and Reynolds, in 1962-63; perpetuated by the Douglas County Surveyor's Office, in 1967; subsequently perpetuated by Schinnell, in 2006; monumented with an iron post, 2½" dia., firmly set, projecting 15" above ground, in a mound of stone, 3 ft. base, 12" high, with a brass cap (properly) mkd from which the remains of the bearing trees reported by White, Beck, and Reynolds
A decayed fir stump, 28" dia., bears S.88°E., 14.5 ft., with a portion of the healed blaze intact. (Orig)cont

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 700640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 1; & S. 6 of T. 26-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A cedar, 31" dia., bears S.53½°E., 27.1 ft., with a healed double blaze.
A fir stump, 57" dia., bears N.2°W., 31.0 ft., no marks visible.
and a bearing tree mkd. by the Douglas Co Surveyor's Office
A hemlock, 16" dia., bears N.51½°W., 30.2 ft., with no marks visible on partially healed double blaze.
and a bearing tree mkd. by Schinnell
A hemlock, 25" dia., bears S.78°W., 9.0 ft., with axe marks visible on bark.
Corner is located on top of a ridge, bears N.80°E. & S.75°W.