

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 700700

PRIMARY CORNER DESCRIPTION Tsp. Cor. NE Cor. Sec. 1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original-Addison R. Flint, Under Contract #56 dated March 1, 1855 (DCSO records, Volume 10 Pages 4179-80)

-----  
Set post, cor. to secs. 1, 36, 6 and 31, from which  
A R.Fir 7" dia. bears S.5°W., 57 lks. dist.  
A R.Fir 40" dia. bears S.36°E., 64 lks. dist.  
A Maple 2" dia. bears N.35°E., 42 lks. dist.  
A Maple 2" dia. bears N.51°W., 26 lks. dist.  
A mound of stone around the post.

Fd. OK by Laban Wheeler under Contract #467 dated 1883.  
(DCSO records, Volume 9 Pages 3584-85)

GL0 Dependent Resurvey by Charles M. Collier, under  
Instructions dated May 12, 1913. (DCSO records, Volume 10  
Pages 4254-55)

-----  
Intersect the point for the cor. of Tps. 25 and 26 S., Rs. 2  
and 3 W., located by reference to the SE. bearing tree and  
further identified by a mound of stone as described by the  
surveyor general; all other traces of the cor. have  
disappeared. I re-establish this cor. in its original  
position, as follows:

Set a basalt stone 24x10x10 ins., 18" in the ground, for Tps.  
cor. marked with 6 notches on each edge and rebuild the old  
mound of stone around cor.; from which

A fir 14" dia. bears N.31°E., 36 lks., marked T 25 S R  
2 W S 31 BT.

A Fir 40" dia., bears S.36°E., 64 lks., marked T26S R2W  
S 6 BT. (Original bearing tree)

A Laurel 5" dia., bears S.85°W., 29 lks., marked T 26 S  
R 3 W S 1 BT.

A Fir 10" dia., bears N.22°W., 31 lks. marked T 25 S R  
3 W S 36 BT.

This corner stands at head of steep ravine, course W. Rock  
Creek is about 12 chs. to west.

GL0 Dependent Resurvey by Norman D. Price, Under Special  
Instructions dated April 5, 1940 (DCSO records, Volume 27  
Page 11508)

-----  
The original corner of Tps. 25 and 26 S., Rs. 2 and 3 W.,  
which was established by Addison R. Flint in 1855, and which  
was perpetuated by Chas. M. Collier, Surveyor, in 1913, where  
I find a basalt stone 24x10x10 ins., firmly set, mkd. with 6  
notches on N., S., E., and W. edges. At point for corner,  
continued next page

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 700700

PRIMARY CORNER DESCRIPTION Tsp Cor NE Cor Sec 1

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Set an iron post, 3 ft. long 3" dia., 28" in the ground, with the marked stone deposited at the base, for cor. of Tps. with brass cap marked:

T25S
R3W   R2W
S36   S31
S1   S6

1943

from which

A Fir 20" dia., bears N.30°E., 36 lks., with blaze healed.  
( A Collier BT)

A Fir 46" dia., bears S.36°E., 64 lks., with partial scribe marks on old bark blaze. (A Flint bearing tree which I reblaze and remark T 26 S R 2 W S 6 BT).

A dead Madrona 6" dia., bears S.85°W., 31 lks. mkd. T 26 S R 3 W S 1 BT. (Collier BT.)

A Fir 16" dia. bears N.23¼°W., 31 lks. with blaze healed.  
( A Collier BT)

A Fir 18" dia., bears S.77°W., 61 lks., mkd. T 26 S R 3 W S 1 BT. (New BT)

Fd. Brass Cap and 5 BTs, Daniel Berry; Wofford; Popken; Baughman, 1972-75 (DCSO records, Volume 36, Pages 15108-09)

Found OK, Glenn Baughman, March 1976, C.S. File 58/100-1  
Fd. Ok by D.Edwards, 4/1998 - M128-61

Kevin Schinnell - For: Rosboro Lumber Co. - 1/2006 - M 149-35

Found - 3½" brass monument on 3" IP& accessories as follows:

24" fir N.20°W., 19.21'

47" fir S.88°E., 19.67'

New - 14" fir S.32°E., 25.84'

Note - All accessories repainted and flagged at this time

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2919, surveyed May 2018/July 2020 - (DCSO records Vol. 59 Page(s) 23917-8)

The cor. of Tps. 25 and 26 S., Rs. 2 and 3 W., perpetuated by Schinnell, in 2006; monumented with an iron post 3" dia., firmly set projecting 20" above ground, in a mound of stone, 3 ft. base, 18 ins. high with a brass cap (properly) mkd. from which an original bearing tree

A fir, 51" dia. bears S.36°E., 42.2 ft with a healed blaze and the bearing trees mkd. by Collier in 1913-14

A fir, 36" dia., bears N.30°E., 23.8 ft., with a healed blaze.

A fir, 27" dia., bears N.23¼°W., 20.5 ft., with a healed blaze.

Continued next page

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 700700

PRIMARY CORNER DESCRIPTION Tsp. Cor. NE Cor. Sec. 1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and the remains of a bearing tree mkd. by Price in 1943-44  
A fir stump, 30" dia. bears S.67¼°W., 40.3 ft., with axe marks visible on bark. (Record, bears S.77°W.)  
and a BT mkd. by person(s) unknown, reported by Schinell  
A fir, 49" dia., bears N.85¼°E., 21.5 ft., with axe marks visible on bark.  
and the remains of a bearing tree mkd. by Schinell  
A fir snag, 14" dia., bears S.35°E., 26.5 ft., with axe marks visible on open blaze.  
and a new bearing tree  
A fir, 12" dia., bears S.56°W., 27.4 ft mkd T26S R3W S1 BT  
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.