

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 917060

PRIMARY CORNER DESCRIPTION Angle Point #6 Power Reserve, S.9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Segregation Survey of Power Reserve, Sec. 9 by  
Fred Mensch, Under Special Instructions dated July 14,  
1924 (DCSO records, Volume 11 Page 4419)

-----  
To Angle Point #6, Set an iron post 3 ft. long, 1" dia., 27"  
in the ground, for Angle Point #6, Power Reserve, with brass  
cap marked:

A P 6 /  
P R /  
1924

from which

An Ash, 14" dia., bears N.63°W., 13 lks. dist., mkd.  
A P 6 P R B T.

-----  
Doug. County Surveyors Office - John M. Powell; J. Heritage  
Dec. 3, 1971 - C.S. File 54/7-65

-----  
Found - 1924 GLO Brass cap firmly set and properly marked.  
14" Ash now 20" N.63°W., 8.6 ft. Shows scar.  
New BTs - 14" B.Oak N.41°W., 21.8 ft. scribed PR AP6 CS BT.  
This corner lies North 33.0 ft. and West 25.0 ft. from center  
of road.