

TOWNSHIP 26 RANGE 04E POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 18; 12 & 13 T26-4E

Alias \_\_\_\_\_ Description (Sec 7 T26-4E = PB 38)  
Alias \_\_\_\_\_ Description (Sec 18 T26-4E = PB 39)  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman under Special Instr. dated Dec. 27, 1920, Group No. 64; surveyed Aug. 1930/June 1931 - (DCSO records Vol. 23 Page 9739-40)

-----  
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 7, 12, 13, & 18, with brass cap mkd:

T26S  
R3E|R4E  
S12|S 7  
S13|S18  
1930

raise a mound of stone 3 ft. base, 2 ft. high, W of cor.  
No trees within a reasonable distance.

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - Debbie Stewart - Sept. 24, 1981 - C.S. File 61/27-54

-----  
Found - Orig. 1930 Brass Cap firmly set, protruding 12" out of the ground, properly marked, with mound of stone at West side of cap, 3 ft. dia. at base, & 1 ft. dia. at top, 2 ft. high.

No trees were marked on orig. survey.

- New BTs- 14" Fir bears S.48°W., 8.0 ft., scribed "T26S R3E. S13 CS BT" in double blaze.  
29" Fir bears N.50°W., 31.3 ft., scribed "T26S R3E S12 CS BT" in bark.  
24" Fir bears N.12°E., 16.5 ft., scribed "T26S R4E S7 CS BT" in bark.  
11" Fir bears S.44°E., 18.2 ft., scribed "T26S R4E S18 CS BT" in double blaze.