

PRIMARY CORNER DESCRIPTION NW Cor. Singleton DLC #50

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Aaron Bowser under contract dated April 1856  
Survey approved 1858

-----  
Set post from which  
    A B.Oak 10" dia. bears S.45°E., 24 lks.  
    A B.Oak 7" dia. bears N.30°W., 75 lks.

B.A. Shaner, LS #430 - For: J. A. Barnes - July 27, 1981  
C.S. File 58/229-41

-----  
Found - No monument found.  
    18" B.Oak, orig. BT, with definite face in at 85 to  
        90 years & an older face in at 125 to 130 years  
        badly rotted, probable original face, but no  
        scribes visible on either face, bears S.45°E.,  
        15.8 ft.  
    36" Maple Orig. BT, with old face bears N.30°W.,  
        47.0 ft. (Rec. BT was a 7" B.Oak, N.30°W., 49.5  
        ft.)  
    Creek, 10.0 ft. wide, course NW is 27 ft. East of  
        this corner. (Record, 38.3 ft.)  
New BTs - 10" W.Oak BT, I scribed "T26S R4W NWC DLC 50 BT"  
        bears S.85½°E., 96.4 ft.  
    14" Alder BT, I bark scribed "T26S R4W DLC 50 BT"  
        bears N.40°W., 75.2 ft.  
Set at the NW Cor. of DLC #50, a 2" I.P. with a 2½" brass cap  
marked: "T26S R4W WM ● — N.W.C. D.L.C. No. 50 RLS 430 1981"  
    |  
The courses for the above accessories go from this set B.C.  
This corner restoration is part of a road right of way survey  
which probably will be competed at a later date.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -  
Stephen J. Flause - 10/10/2000 - C.S. File 66/16-49A

-----  
CONDITION REPORT on corner position determined in 1981 by  
Shaner

Fd - 1981 BC/IP 10" below ground.  
    10" B.Oak now badly rotted.  
    3 ft. high Oak shell bears S.45°E., 15.8 ft. (Agrees  
        w/orig. rec.)  
    7" B.Oak noted as a 36" Maple in 1981, now 38" dia.,  
        hollowed out & rotted Maple bears N.34°W. 47.0'  
        (Orig. rec. N.30°W. 49.5') 1981 rec. N.30°W., 47.0')  
    10" now 12" W.Oak with a fully healed single blaze,  
        bears S.85½°E., 96.4 ft. (1981)

continued next page

TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 050020

PRIMARY CORNER DESCRIPTION NW Cor. Singleton DLC #50

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

14" now 16" alder with bark scribing "T26S R4W NWC  
DLC 50 BT" bears N.40°W., 75.2 ft. (1981)  
Corner is approx. 1½ ft. SW of SW corner of bridge  
over creek.  
Note - We re-tag 1981 BTs.