

TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 052010

PRIMARY CORNER DESCRIPTION NE Cor. Oden DLC #52

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Aaron Bowser under contract dated April, 1856
Survey approved 1858

Set post in prairie, deposited stone 15 x 12. Raised mound
with trench as per instructions.

Victor McLind - For: Janice Stull - July 1973 - M 50-32

Set by proportionment - 5/8" x 30" iron rod.

Doug. Co. Surveyors Office - Gary L. Langlitz - Peter Earle
January 20, 1975 - C.S. file 57/17-9

Found - 5/8" Iron rod set by McLind in 1973.
At corner point, we set a 1" x 30" Iron pipe 27" in the
ground with brass cap attached marked:
County Surveyors T 26 S
Office
1975
NE
DLC
52
R 4 W
We place the iron rod alongside the brass cap & mark the
following New BTs:
A 27" forked W.Oak (dia. measured below fork) bears
N.80°E., 194.5 ft. scribed "NE DLC 52 CS BT".
A 15" B.Oak, one of four sprouts growing on a common
base, bears N.8°E., 175.5 ft. scribed "NE DLC 52
CS BT" (bearing & distance taken to center of common
root crown)
We place a steel fence post with survey marker sign attache,
1.0 ft. North of corner. Compass Dec. setting: 20° East.

Fd. OK - K.DeGroot - Aug. 1995 - 1995-0112 A&B
Found OK by H. Pieske, Sept. 2000 - 2000-0062 A&B