

TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 052020

PRIMARY CORNER DESCRIPTION N NW Cor. Oden DLC #52

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Aaron Bowser under contract dated April, 1856  
Survey approved, 1858

-----  
Set post in prairie, deposited stone 12 x 13. Raised  
mound with trench as per instructions.

Victor McLind, LS #934 - For: Janice Stull, July 1973  
M 50-32

-----  
Set by proportionment, 5/8" x 30" Iron Rod.

Doug. Co. Surveyors Office - Gary L. Langlitz; Peter Earle  
January 20, 1975 - C.S. File 52/17-10

-----  
Found - 5/8" Iron rod set by McLind, 1973.  
At the corner point, we set a 1" x 30" Iron pipe with brass  
cap attached marked: County Surveyors T 26 S  
Office | NNW  
1975 | DLC  
| 52  
R 4 W

We place the found Iron rod alongside and set a steel fence  
post with survey marker sign attached 1 ft. north of corner.  
There are no suitable trees near.

FD. OK - K.DeGroot - Aug. 1995 - 1995-0112 A&B