

TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 30; & S. 25 of T26-5

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - James E. Freeman Contract #1 dated May 1851  
(DCSO records, Volume 11 Page 4423 and 4425)

-----  
Set ¼ sec. post, from which  
    A B.Oak 12" dia. bears N.40°E., 75 lks. dist.  
    A B.Oak 12" dia. bears S.17°W., 337 lks. dist.

L.G. Hicks - For R.F. and Mae Lewis - "Plat G, Lewis Addn.  
to Sunshine Ranch (now vacated) - Volume 5 Pg. 22, 10/1914

-----  
Sandstone 8" x 8" x 14", 1/4 Sec. cor. bet. 25 and 30

James W. Byron, Deputy - Milo Godfrey; Clete Putnam  
July, 1960 - C.S. File 49/125-6

-----  
Found - Stone at corner as recorded.  
        10" now 14" B.Oak East 37.7 ft. We opened old  
            scarred section & find good reverse scribing  
            "X R P".

        Also fine base of Oak stump N.40°E., 48.6 ft.  
        No trace of S.W. BT.

Set - Brass cap alongside corner stone & marked: County  
        Surveyor's Office, 1960 ¼ S25|S30 T26S  
  R5W R4W

New BTs - 10" B.Oak bears N.62°E., 23.0 ft. scribed ¼ S30 CSBT  
          22" Pine bears N.10°W., 50.4 ft. scribed ¼ S25 CS BT