

TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 18; & 13 of T26-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - James E. Freeman under contract #1 dated May 1851
(DCSO records, Volume 11 Page 4422 and 4425)

Set ¼ sec. post, from which
 A B.Oak 12" dia. bears N.8°W., 320 lks. dist.
 Made trench as per instructions

James W. Byron, Deputy Co. Surveyor - Milo Godfrey; S.A.
Bilow For Office Records - December 1958 - C.S. File 49/128-2
M 13-57

Found - Orig. 12" now 42" B.Oak N.7°48'W., 211.2 ft. I open
 and find good scribings "¼S".
Set brass cap at cor. mkd: ¼ S13|S18 T26S County Surveyor's
 R5W R4W Office, 1958
New BTs - 12" W.Oak bears S.81°40'W. (true) 91.5 ft. scribed
 ¼ S13 CS BT.
 9" W.Oak bears N.23°E., (true) 104.5 ft. scribed
 ¼ S18 CS BT.

BLM Dependent resurvey by Timothy J. Moore, A. Bert Skeesick,
Cadastral Surveyors and Robert H. Browning, Survey Tech,
under Group No. 2065 surveyed May 2004/April 2005 - (DCSO
records Vol. 57 Page(s) 22451)

The ¼ sec. cor. of secs. 13 and 18, on the E. bdy. of the
Tp., perpetuated by Byron, in 1958, monumented with an iron
pipe, 1¼" dia., firmly set, projecting 10" above the ground,
with brass cap (properly) mkd.
from which the remains of the original bearing tree
 An oak, 48" dia., bears N.8°W., 211.2 ft., with
 fragmentary scribe marks visible on a partially
 opened blaze.
and bearing trees mkd. by Byron
 An oak, 14" dia., bears N.23¼°E., 104.7 ft., with a
 healed double blaze.
 An oak, 18" dia., bears S.81½°W., 91.2 ft., with a
 healed double blaze.