

TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Cor Secs 7 & 18; & 12 & 13, T26-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO original survey by James E. Freeman, Deputy Surveyor, under Contract No. 1, dated May 28, 1851 - (DCSO records Vol. 11 Pages 4421 & 4422)

-----  
**(Witness corner 24.18 chs SOUTH of true position)**

Page 4421

Sec. cor. is inaccessible. The river bluff, is W of cor. and extends in the form of a crescent from one witness cor. to the other.

Page 4422

South on the West Bdy of Sec. 18  
24.18 chs

Set Witness cor. from which,

A B.Oak, 9" dia., bears S.48°E., 48 lks.

A Y.Pine, 48" dia., bears N.15°W., 16 lks.

-----  
GLO original survey by Robert Elder & Henry S. Gile, Deputy Surveyors, under Contract No. 31, dated April 7, 1853 - (DCSO records Vol. 11 Page 4482)

-----  
**(Witness corner 9.46 chs West of true position)**

Intersect E Bdy . . .

N.87°7'W. on true line between Secs. 12 & 13  
9.46 chs

Set Wit. post of Sec. cor. (at top of bluff) from which

A Y.Oak, 15" dia., bears N.6°E., 16 lks.

A Y.Oak, 15" dia., bears S.7°E., 20 lks.

-----  
Douglas Co. Surveyors Office - Milo Godfrey - Feb. 1964 -  
C.S. File 49/125

-----  
Searched for, not found.

Wit. cor. S12/S13 (9.46 chs. W of sec. cor.)

Wit. cor. S13|S18 T26S R's 4 & 5 W (24.18 chs S of sec. cor.)