

TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 162500

PRIMARY CORNER DESCRIPTION Meander Cor. right bank, U River

Alias 859480 Description M.C. on Section line 7 & 18
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 11 Page 4458)

Set meander post on east or right bank of Umpqua River,
from which,
 A W.Oak 7" dia. bears N.52°W., 39 lks. dist.
 A B.Oak 8" dia. bears S.45°E., 50 lks. dist.

James W. Byron, Deputy - Milo Godfrey; S.A. Bilow -
December 9, 1958 - C.S. File 49/125-4

Found - Orig. 7" now 15" W.Oak N.52°W., 25.7 ft., I open &
 find good reverse scribing "BT".

No trace of orig. SE BT.

Note, Corner at edge of bluff, I set WIT. COR. 14 ft. East.
Set brass cap at wit. cor. mkd: County Surveyors Office 1958
 Wit. Cor. 14' West to MC / S 7 T26S R4W
 / S 18

This M.C. 17.63 chains West of Section corner for 7,8,17,18.
New BTs - 15" W.Oak bears S.25½°E., 32.5 ft. scribed WC MC
 S 18 CS BT.
 15" W.Oak bears N.30°W., 42.4 ft. scribed WC MC S7
 CS BT.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 5/24/1999 - C.S. File 66/12-20

Found - 2½" brass cap on a 1½" O.D. iron pipe, protrudes 16"
 above ground. 1958

No OBTs found.

15" now 21" dia., W.Oak with a fully healed double
 blaze bears S.25½°E., 32.5 ft. (Agrees w/rec)
 1958

15" now 17" dia., W.Oak with a fully healed double
 blaze bears N.30°W., 42.4 ft. (Agrees w/rec)
 1958

Set - 5" dia., W.Oak double blaze & scribed "X CS BT"
 bears S.86°W., 10.2 ft.

5/8" I.R. at fence corner protrudes 2" above ground,
 bears S.39°E., 71.2 ft.

Corner lies near edge of bluff.

Fd. Ok by R. Quimby 2/2007 - 2007-0029A&B