

TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30, 31 & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 11 Page 4452)

Set post corner to secs. 29, 30, 31 and 32, from which
A W.Oak 5" dia. bears S.38°E., 4 lks. dist.
A W.Oak 4" dia. bears S.35°W., 4 lks. dist.
A W.Oak 6" dia. bears N.32°W., 15 lks. dist.
A W.Oak 8" dia. bears N.43°E., 34 lks. dist.

H.L. Eppstein, Co. Surveyor - Wit: W.L. Dolan; T.D. Boise
June 2, 1925 - C.S. File 2/44

I set corner from one old tree with scribe marks on it.
One other tree standing, no scribe marks.
Set 4x4x36" Oak stake and mkd. new trees as follows:
W.Oak 12" dia. bears S.54°E., 36 ft.
W.Oak 10" dia. bears S.31°W., 38 ft.
W.Oak 24" dia. bears N.45°W., 297 ft.
No tree in Sec. 29 near.

James W. Byron, Dep. Co. Surveyor - Ray Irving; John Fee
April 1955 - C.S. File 46/122 (pg 6)

Found - Hub and tack at cor. under E-W fence, and all trees
alive & in good condition as renewed previously
All check for bearings and dists. Blazes have
grown over. I did not cut out.
Set 1" Iron pipe with brass cap mkd S30|S29 T26S R4W County
Surveyors Office S31|S32 1955.
(Var. 21¼°)

Fd. Ok by Neil Hibbs Feb. 2005 - 2005-0047 A&B