

TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 11 Page 4456)

Set 1/4 sec. post from which
 A W.Oak 8" dia. bears S.20°E., 140 lks. dist.
 A W.Oak 12" dia. bears S.5°W., 895 lks. dist.

James W. Byron, Deputy - For Allenby & Nye, Whistlers Park
Estates - Milo Godfrey; S.A. Bilow, witnesses - March 10,
1959 - C.S. File 49/115

Found - Orig. 8" now 20" W.Oak S.20°E., 92.4 ft., I open &
 find good scribing "1/4S".
 Now 36" W.Oak S.4°W., 551.0 ft. record, 12" W.Oak
 S.5°W., 590.7 ft. I open, center rotted, no
 scribing found.

I use orig. SE BT and Set brass cap at cor. mkd: County
 Surveyors Office 1959 1/4 S18|S17 T26S R4W
New BTs - 20" B.Oak bears N.21°E., 129.0 ft. scribed 1/4 S17
 CS BT.
 20" W.Oak bears S.20°E., 92.4 ft. scribed 1/4 S17
 CS BT.

Sketch in C.S. file for tie to 1/4 corner.

Fd. Ok by Herman Pieske - Dec. 1998 - M 130-79
Fd. Ok by Neil Hibbs Feb. 2005 - 2005-0047 A&B