

TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 11 Page 4457)

Set post corner to secs. 7,8, 17 and 18, from which
A B.Oak 10" dia. bears N.35°W., 80 lks. dist.
A B.Oak 15" dia. bears N.2°E., 79 lks. dist.
A B.Oak 6" dia. bears N.58°E., 158 lks. dist.
A B.Oak 12" dia. bears S.87°W., 226 lks. dist.

James W. Byron, Deputy Co. Surveyor - M. Godfrey; S.A. Bilow
December 9, 1958 - C.S. File 49/125-3

Found - Orig. 15" now 24" B.Oak N.2°E., 52.1 ft. I open &
find good scribing "S8".
Old stump holes that check bearing & distance for
original NE & NW BTs.
No trace of orig. SW BT.

Set brass cap at corner mkd: T26S R4W S 7 | S 8 County Surveyor
S18 | S17 Office, 1958

New BTs - 8" W.Oak bears N.27°E., 57.0 ft. scribed S 8 T26S
R4W CS BT.
15" B.Oak bears N.59°W., 90.8 ft. scribed S 7 T26S
R4W CS BT.
12" B.Oak bears S.19½°W., 83.0 ft. scribed S18 T26S
R4W CS BT.
12" B.Oak bears S.26°E., 11.3 ft. scribed S17 T26S
R4W CS BT.

Found OK, January 1971. J.M.P. C.S. 56/1-12
Fd. Ok M117-78 Aug. 93
Fd. Ok by R. Quimby 2/2007 - 2007-0029A&B
Fd. ok by K. DeGroot - 10/2007 - 2007-0140