

TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 11 Page 4453)

Set ¼ sec. post to which there being no trees within
reasonable distance, I raised a mound as per instructions.

William Ruppert, PLS #866 - For: Gamegan, Wilcox & Weathers
May 1978 - RM 3-15

Set - 1" x 30" galv. steel pipe with 2½" brass cap mkd:
T26S R4W ¼ S29 S32 PLS 866 1978.

Fd. Ok by Neil Hibbs Feb. 2005 - 2005-0047 A&B

Douglas Co. Surveyor's Office - Crew: Jeff Lorsung -
12/31/2024 - C.S. File 67/59-36

Found - 2½" brass cap (Prop MKD)
New - Power pole marked B-4010 N.48°W. 23.0' add PK.
T.post 0.5' NW
Set ⅝"x30"I. rods with DCSO plastic caps;
East 6.0' West 5.0'
Note - Mon is 5' North of Foster Lane. All trees that
could be marked on private property.
Compass decl. 14¼°E.
O CRS COORDINATE SYSTEM
COTTAGE GROVE-CANYONVILLE ZONE
N 146408-826 E 157103.341