

TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 11 Page 4447)

Set post corner to secs. 28, 29 32 & 33 from which
A B.oak 24" dia. bears N.80°E., 481 lks. dist.
A B.Oak 17" dia. bears N.79°W., 378 lks. dist.
A W.Oak 20" dia. bears S.58½°W., 209 lks. dist.
A W.Oak 18" dia. bears S.11°E., 450 lks. dist.

Douglas Co. Surveyors Office - M. Germond - For: Joseph
Thornton - Feb. 1916 - Vol. 3 Page 6

I reset this sec. cor. with a S.Stone 6"x15"x20" and note
three old "B°T" still in evidence.

H.L. Eppstein, Co. Surveyor - Wit: W.L. Dolan; T.D. Boise
June 2, 1925 - C.S. File 2/44

Set stone 8 x 12 x 15" from 2 old BTs, still standing in good
condition. Marked trees for tree gone as follows:
A Cedar 12" dia. bears S.85°E., 123 ft.
A Fir 12" dia. bears N.58°E., ~~262.6 ft.~~ 267.2 ft. per
research 8/5/2025 JC DCSO

James W. Byron, Dept. Co. Surveyor - Ray Irving; John Fee -
April, 1955 - C.S. File 46/122 (pg 9)

Found - Sandstone rock 8" x 12" x 15" at corner. Also both
trees as renewed previously. The Cedar checks for
bearing & distance. The Fir checks for bearing only
measures 267.2 ft. Record, 262.2 ft. (**see above**)
Set 1" iron pipe with brass cap mkd. 29|28 T26S R4W Sec. Cor.
1955, County Surveyors Office 32|33
Placed sandstone rock alongside brass cap.
Blazed & scribed:
12" W.Oak N.2½°W., 115.8 ft. S 29 T26 R 4 CS BT.

Fd. Ok by Neil Hibbs Feb. 2005 - 2005-0047 A&B
Fd. BC by M Heimbürger - 1/2021 - C.S. File 65/107-6