

PRIMARY CORNER DESCRIPTION 1/4 Cor. for 21 and 28

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

<p>Original - Addison R. Flint, Contract #56 dated March, 1855 (DCSO Records, Volume 11 Page 4448)</p> <p>-----</p> <p>Set 1/4 sec. post from which A W.Oak 8" dia. bears S.66°W., 203 lks. dist. A W.Oak 6" dia. bears N.76°W., 195 lks. dist.</p>	
<p>N.E. Richardson, Deputy - Wit: M.E. Godfrey; L.S. Kershner July 1947 For: Frank Sinnott - C.S. File 39/90 & M 13-45</p> <p>-----</p> <p>Set a 1" x 36" Iron pipe 24" in the ground with a brass cap marked: 1/4 Cor. 21, 28, T 26 S R 4 W County Surveyors Office from which: An Old BT bears S.76°W., 195 lks. An Old BT bears N.66°W., 203 lks. A W.Oak 15" dia. bears S.28°W., 29.5 ft. dist. A W.Oak 16" dia. bears N.35°W., 23.4 ft. dist.</p>	
<p>Found OK, K. DeGroot, Jan. 1984 - M 96-17</p>	
<p>Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 10/25/2000 - C.S. File 66/18-1 A-F</p> <p>-----</p> <p>Found - 1947 DCSO BC/IP protrudes 10" out of ground COUNTY SURVEYORS (Note: BC orientated SEC South. Marked 1/4 S 28 Correctly) S 21 OFFICE</p> <p>8" now 24" dia., 2 ft. high rotted Oak stump showing evidence of a previous axe search, no scribing found, bears N.59°W., 134.0 ft. (Rec. N.66°W., 134.0 ft) OBT</p> <p>6" now 26" dia., W.Oak with a previously opened unhealed blaze, scribing visible "BT", bears S.83 1/2°W. 128.7 ft. (rec. S.76°W., 128.7 ft) OBT</p> <p>Position of corner in 1947 apparently set by Dist. Int. from OBTs and old rail fence. Poor brg. relationship between OBTs.</p> <p>See sketch in CS 39/90 (Also copy in CS 66/18-1)</p> <p>15" now 17" W.Oak with a fully healed blaze, bears S.30 1/2°W., 30.0 ft. (Rec. S.28°W. 29.5 ft.) 1947</p> <p>16" now 21" dia., W.Oak w/fully healed blaze, bears N.35°W., 24.0 ft (rec. N.35°W., 23.4 ft) 1947</p> <p>New - 14" dia., D.Fir double blazed & scribed "1/4 S21 CS BT" bears N.5°E., 3.8 ft. Dec. 17 1/2°E. continued next page</p>	

TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for 21 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Note - East - West fence line is 10 ft. South of BC/IP.
Position of corner perpetuated as set in 1947.
Unresolvable Brg & Dist. errors in orig. notes.
SEE CS 66/18-1B for history of the corner and of the
changes made to the DCSO typed line notes. Also
for calculations made by RWS.