

TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Sec Cor for 27, 28, 33 & 34

Alias <u>049040</u>	Description <u>Int "I" Cor DIC #49</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Contract #56 dated March 1855 (DCSO records, Volume 11 Page 4441)

-----  
Set post corner of Secs. 33, 34, 27 and 28, from which  
A W.Oak 12" dia. bears S.70°W., 160 lks. dist.  
A W.Oak 5" dia. bears N.79°W., 194 lks. dist.  
An Ash 15" dia. bears S.51°E., 130 lks. dist.  
An Ash 6" dia. bears N.68°E., 472 lks. dist.

M. B. Germond, Co. Surveyor - For: Joseph Thornton, Feb. 1916 Field Book 74 Pgs. 26-28; C.S. File 1/41; Vol. 3 Pg. 6

-----  
After diligent search, I locate the cor. of secs. 17, 28, 33 & 34. The large Ash BT stump is still in evidence & the letters "BT" discernible. I Re-establish this cor. with a Sandstone 5" x 12" x 18".

J.W. Cole, Co. Surveyor, For: Oak Ck. Rd. petition - Asher, Agee & Singleton - Feb/March 1923 - C.S. File 8/10

-----  
Found - Rock set by Germond from orig. Ash BT., bears S.15°E. 8.6 ft. remarked CS BT.  
Stump of orig. BT bearing scribe marks bears N.70°W., 203 ft.  
New BTs - A W.Oak 18" S.21°15'W., 58.0 ft.  
A W.Oak 12" N.54°W., 34.8 ft.

James W. Byron, Dep. Co. Surveyor - Ray Irving; John Fee - April 1955 - C.S. File 46/122 (pg 13 & 17)

-----  
This sec. cor. was renewed by Cole in 1923 from stone set by Germond & calls that had been mistakenly copied from orig. notes. I find stool of Ash on right bank of stream which Cliff Agee states is the location of the orig. BT, a 15" Ash S.51°E. 85.8 ft. The 18" now 30" W.Oak, Cole scribed is standing & in good condition & shows good blaze. We do not open. Using Cole's distance & bearing to his corner checks his distance & bearing to stool of Ash on which Cole states he found scribing. I use stool of Ash, S.51°E., 85.8 ft. to locate corner.  
(Continued Next page)

TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Sec Cor for 27, 28, 33 & 34

Alias 049040 Description Int. I Cor. DLC #49  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Set 1" Iron pipe with brass cap mkd: County Surveyors Office  
1955 S28|S27 T 26 S, R 4 W.  
S33|S34

Blazed and Scribed:  
30" W.Oak S.22½°E., 106.8 ft. mkd. T 26 S, R 4 W., S 34  
CS BT. This is the same BT Cole scribed in 1923.  
24" W.Oak T 26 S., R 4 W S 28 CS BT. (Distance ?)  
No other trees available.

FD. OK - K.DeGroot - Aug. 1995 - 1995-0112 A&B

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -  
Stephen J. Flause - 10/11/2000 - C.S. File 66/16-50

-----  
Found - 1955 DCS0 brass cap iron pipe, protrudes 12" above  
ground.  
30" now 35" dia., W.Oak with a fully healed blaze,  
bears S.24°E., 106.8 ft. (1955 rec. S.22½°E.,  
106.8 ft.)  
Possible 1955 24" W.Oak now 32" dia., with a fully  
healed blaze, we single blaze 4½ ft. above  
ground and scribe "X CS BT" bears N.77¼°W.,  
203.0 ft.  
No other OBTs found.  
New - 11" W.Oak double blazed & scribed "T26S R4W S27 CS  
BT" bears N.73°E., 138.2 ft.  
10" Ash double blazed & scribed "T26S R4W S33 CS BT"  
bears S.45°W., 115.7 ft.  
Note - Found evidence of old Ash at rec. S.51°E., 85.8 ft.

Fd. ok by Dave Beedle, 11/2007 - 2008-0005