

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 11 Page 4442)

Set post corner to secs. 21, 22, 27 and 28, from which
A B.Oak 25" dia. bears S.68°W., 385 lks. dist.
A B.Oak 16" dia. bears S.71°E., 728 lks. dist.
A B.Oak 18" dia. bears N.42°W., 295 lks. dist.
A W.Oak 16" dia. bears N.35°E., 60 lks. dist.

James W. Byron, Deputy Co. Surveyor - Ray Irving; John Fee
April, 1955 - C.S. File 46/122 (pg 10)

Found - Original BT, 18" B.Oak N.42°W., now 35", which I
open & find scribe S 21.
Orig. BT, 16" W.Oak now 24" shows old blaze, center
rotted, no scribing visible.
Make record distance intersection to locate corner.
The Orig. 18" B.Oak now bears N.45°W.
The Orig. 16" W.Oak now bears N.46°E.
Set 1" Iron pipe with brass cap mkd: 21|22 T 26 S R 4 W County
Surveyors Office, 1955 28|27
Blaze & scribe:
18" R.Fir N.87°E., 14.0 ft. S 22 T26S R4W CS BT.
14" R.Fir S.33°W., 6.3 ft. S 28 T26S R4W CS BT.
10" W.Oak S.62°E., 32.7 ft. S 27 CS BT.
12" R.Fir N.25°W., 31.6 ft. S 21 T26S R4W CS BT.

James W. Byron, Deputy - M.Godfrey; C.Putnam - Feb. 8, 1961
C.S. File 49/125-7

Found - 1955 DCSO brass cap.
Three BTs as set in 1955. (The Fir to the NE has
been cut, stump still standing.)
Blaze & scribe:
7" B.Oak N.5½°E., 30.0 ft. mkd. "S22 CS BT".

FD. OK - K. DeGroot - Aug. 1995 - 1995-0112 A&B

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 6/4/2001 - C.S. File 66/21-25

Found - 1955 DCSO brass cap/iron pipe, protrudes 14" above
ground. Corner lies near the intersection of
random fence lines.
16" now down & rotted Oak root hole bears N.46°E.,
39.0 ft. (OBT)
Orig. NW BT gone. continued next page

TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

10" now 12" dia, W.Oak with a fully healed blaze,
bears S.62°E., 32.7 ft. (1955)
12" now 33" dia., D.Fir with a fully healed blaze,
bears N.25°W., 31.6 ft. (1955)
1955 NE & SW BTs now gone, root holes at record.
1961 NE BT now gone, root hole at record.
New - 9" B.Oak double blazed & scribed "T26S R4W S28 CS
BT" bears S.33°W., 21.7 ft.
18" dia., D.Fir double blazed & scribed "T26S R4W
S22 CS BT" bears N.36°E., 39.5 ft.
Compass decl. 17½°E