

TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Sec. Cor for 15, 16, 21 and 22

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Contract #56 dated March, 1855  
(DCSO Records, Volume 11 Page 4443)

-----  
Set post corner of secs. 21, 22, 15 and 16, from which  
A B.Oak 15" dia. bears S.77°W., 140 lks. dist.  
A B.Oak 14" dia. bears N.80°W., 135 lks. dist.  
A B.Oak 10" dia. bears N.20°E., 95 lks. dist.  
A B.Oak 8" dia. bears S.25°E., 92 lks. dist.

J.W. Cole, W. Aldrich, & Wolford - Oct. 18, 1920 - F.B. No.  
49 Page 2

-----  
At established cor., trees standing, do not correspond.  
Found - B.Oak, 24" dia., N.1°15'E., 62.7  
B.Oak, \_\_\_ dia., N.81°00'W., 94.7  
B.Oak, \_\_\_ dia., S.84°00'W., 92.4  
Set - 1¼"x36" iron pipe.

N.E. Richardson, Deputy - Wit: Smith and Godfrey - August 23,  
1949 - C.S. File 43/155 and M 13-49

-----  
Found Iron pipe for corner.  
Set New BTs:  
10" Laurel bears N.66°W., 33.9 ft.  
20" Fir bears N.61°E., 42.8 ft.  
26" Fir bears S.71°W., 13.0 ft.  
30" Fir bears S.41°E., 32.2 ft.

Found, J.Byron, 1961 - M 11-80

Doug. Co. Surveyors Office - James Byron and Crew. March 7,  
1963 - C.S. File 49/125-9

-----  
Found - 1" I.Pipe at corner & 10" now 12" Laurel N.66°W.,  
33.9 ft., shows scribing.  
SW, SE. and NE BTs now stumps.  
New BTs - 7" Laurel bears S.70°W., 30.4 ft. scribed S21 T26S  
R4W CS BT.  
8" R.Fir bears N.52°E., 74.9 ft. scribed S15 T26S  
R4W CS BT.

Doug. Co. Surveyors Office - R.B. Kimberling; M.W. Cline  
Sept. 27, 1977 - C.S. File 59/40-25

-----  
Found - 1" I.P. with top bent over and leaning south, 6"  
above ground. Top of I.P. is 0.3 ft. NE of  
Brass cap set from BTs on this renewal. CONT.

